

LKM IR ST DK

Mufa za vtično spojko (zrak) z varovalom

HANSA FLEX

Lastnosti

Način izdelave	mufa za hitri zaklep
Priključek 1	notranji navoj BSP cilindričen
Priključek 2	
Obratovalni tlak	maks. 12 bar
pretok zraka	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
temperatura medija	-20 °C to +70 °C
ohišje	Aluminium, anodised
navoj	Nickel-plated brass
notranji deli	Stainless steel
gumb, ventil	Hardened, galvanised steel
tesnilni material	NBR



Navodilo

Not suitable for hitting / pulsating tools.

Drugi podatki na zahtevo.

Opis

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

Artikel

Opis	Priključni navoj	Priključek	dolžina (mm)	SW (mm)
LKM 06 IR ST DK	G 1/4" -19	G 1/4 female	71,5	21
LKM 10 IR ST DK	G 3/8" -19	G 3/8 female	75,5	21
LKM 13 IR ST DK	G 1/2" -14	G 1/2 female	77,5	24