

# SCHRAUBE M

Vijak z notranjo šestkotno glavo

**HANSA FLEX**


## Lastnosti

**Način izdelave** vijak z notranjo šestkotno glavo

**Standard** DIN 912 (ISO 4762)

**Material:** jeklo 10.9

**Zaščita površine** fosfatirano



## Artikel

Opis	G	L1 (mm)	SW (mm)
SCHRAUBE M 08-25	M 8	25	6
SCHRAUBE M 08-30	M 8	30	6
SCHRAUBE M 08-35	M 8	35	6
SCHRAUBE M 08-40	M 8	40	6
SCHRAUBE M 10-30	M 10	30	8
SCHRAUBE M 10-35	M 10	35	8
SCHRAUBE M 10-40	M 10	40	8
SCHRAUBE M 10-45	M 10	45	8
SCHRAUBE M 10-50	M 10	50	8
SCHRAUBE M 12-35	M 12	35	10
SCHRAUBE M 12-40	M 12	40	10
SCHRAUBE M 12-45	M 12	45	10
SCHRAUBE M 12-50	M 12	50	10
SCHRAUBE M 12-55	M 12	55	10
SCHRAUBE M 12-60	M 12	60	10
SCHRAUBE M 14-45		45	12
SCHRAUBE M 14-50		50	12
SCHRAUBE M 14-55		55	12
SCHRAUBE M 14-60		60	12
SCHRAUBE M 14-65		65	12
SCHRAUBE M 14-70		70	12
SCHRAUBE M 14-75		75	12
SCHRAUBE M 14-80		80	12
SCHRAUBE M 16-50	M 16	50	14
SCHRAUBE M 16-55	M 16	55	14
SCHRAUBE M 16-60	M 16	60	14
SCHRAUBE M 16-70	M 16	70	14
SCHRAUBE M 16-80	M 16	80	14
SCHRAUBE M 16-90	M 16	90	14
SCHRAUBE M 16-100	M 16	100	14
SCHRAUBE M 20-60	M 20	60	17
SCHRAUBE M 20-65	M 20	65	17
SCHRAUBE M 20-70	M 20	70	17
SCHRAUBE M 20-90	M 20	90	17
SCHRAUBE M 20-100	M 20	100	17
SCHRAUBE M 20-110	M 20	110	17
SCHRAUBE M 20-120	M 20	120	17

SW = ključna širina

## Variante izdelka

SCHRAUBE M VZ

## je pribor za naslednje izdelke

FH (3000 PSI) Polovica objemke SAE

FH (6000 PSI) Polovica objemke SAE

VF (3000 PSI) Polna prirobnica SAE

VF (6000 PSI) Polna prirobnica SAE