

HK SAH

valj z votlim batom AI 700 bar

HANSA FLEX

Lastnosti

Izvedba	glava valja, kaljena bat, trdo kromani povratna vzmet
Obratovalni tlak	maks. 700 bar
Material:	aluminij
Zaščita površine	eloksirano
Obseg dobave	s hitro spojko, puša 3/8"-18 NPT



Navodilo

Attention: Please observe separate safety precautions for working with 700 bar equipment (see technical information)!

Opis

Valji z votlim batom so uporabljeni za tlačne in vlečne pomike.

Very low weight (-40% of a comparable steel cylinder)

Enostavna pritrditev z navojem na ohišju valja

batni obročki preprečujejo onesnaženje

zamenljiva naležna glava

Ni primerno za dolgotrajno uporabo z veliko frekvenco ponavljanja.

Artikel

Opis	Hod		Površina (cm ²)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	H (mm)	K (mm)	L (mm)	M	N (mm)	R	S (mm)	T (mm)	Prostornina (cc)	Teža (kg)	
	(kN)	(t)																		
HK SAH 03015	301,8	30	150	44,0	352	502	33,0	130	90	68	32	4,0	55	1.11/13"-16	9	M6	110,0	19	660	11,5
HK SAH 06010	578,0	60	100	84,0	298	398	56,0	175	125	95	37	4,0	80	2.3/4"-16	12	M6	155,0	19	842	19,5