


# HK HM BMM

## gerotorski motor BMM CN

### Lastnosti

Priključek	oljni priključki zadaj: A + B = G 3/8 "; iztok olja = G 1/8"
Izvedba	Economy variant Tesnila NBR Gred Ø 16 mm
Vhodni in povratni tlak z vodom za puščajoče olje max.	140 bar



### Artikel

Opis	pretok max. (L/min)	Iztisnina (cc)	Število bratov min. (rpm)	Število bratov max. (rpm)	vrtljni navor max. (N-m)	Padec tlaka max. (bar)	Pmax. at 0-100 rpm (bar)	Pmax. at 100-300 rpm (bar)	Pmax. at 300-600 rpm (bar)	Pmax. at 600 rpm (bar)	L (mm)	Teža (kg)
HK HM BMM 008	16	8,2	50	1950	11	100	140	90	30	15	105	1,9
HK HM BMM 012	20	12,9	40	1550	16	100	140	90	30	15	107	2,0
HK HM BMM 020	20	19,9	30	1000	25	100	140	90	30	15	110	2,1
HK HM BMM 032	20	31,8	30	630	40	100	140	90	30	-	115	2,2
HK HM BMM 040	20	39,8	25	500	45	90	140	90	30	-	118	2,3
HK HM BMM 050	20	50,3	20	400	46	70	140	90	-	-	123	2,4

max. pressure on shaft seal (without leak oil line) or pressure in leak oil line – vrednosti navora in padca tlaka veljajo za neprekinjeno delovanje

### Pribor

HK EPMM F prirobnica za motor z gerotorjem