

### Osobine

|                             |   |
|-----------------------------|---|
| <b>Priključak 1</b>         | NPT spoljni navoj                                 |
| <b>Oblik zaptivke 1</b>     | zaptivanje preko navoja                           |
| <b>Priključak 2 + 3</b>     | metrički spoljni cilindrični navoj                |
| <b>Oblik zaptivke 2 + 3</b> | 24° unutrašnji konus                              |
| <b>Konstrukcija</b>         | Uvrtni navojni spoj                               |
| <b>Konstrukcija</b>         | L oblik   |
| <b>Obim isporuke</b>        | Nastavak sa preklopnom navrtkom i reznim prstenom |
| <b>Materijal</b>            | čelik   |
| <b>Površinska zaštita</b>   | galvanska prevlaka                                |



### Napomena

Molimo Vas da napomene za montažu, ugradnju, opterećenje pod pritiskom i dozvoljene radne temperature nađete u tehničkim informacijama o navojnim spojevima za cevi.

### Artikal

| Naziv       | Seriya | Radni pritisak bar | Ø d2 (mm) | G1               | i (mm) | L3 (mm) | L4 (mm) | L5 (mm) | SW (mm) | S1 |
|-------------|--------|--------------------|-----------|------------------|--------|---------|---------|---------|---------|----|
| LN 04 LL    | LL     | PN 100             | 4         | 1/8" -27 NPT     | 8      | 21      | 11,0    | 17      | 9       | 10 |
| LN 06 LL    | LL     | PN 100             | 6         | 1/8" -27 NPT     | 8      | 21      | 9,5     | 17      | 9       | 12 |
| LN 08 LL    | LL     | PN 100             | 8         | 1/8" -27 NPT     | 8      | 23      | 11,5    | 20      | 12      | 14 |
| LN NW 04 HL | L      | PN 315             | 6         | 1/8" -27 NPT     | 8      | 27      | 12,0    | 20      | 12      | 14 |
| LN NW 06 HL | L      | PN 315             | 8         | 1/4" -18 NPT     | 12     | 29      | 14,0    | 26      | 12      | 17 |
| LN NW 08 HL | L      | PN 315             | 10        | 1/4" -18 NPT     | 14     | 30      | 15,0    | 27      | 14      | 19 |
| LN NW 10 HL | L      | PN 315             | 12        | 3/8" -18 NPT     | 12     | 32      | 17,0    | 28      | 17      | 22 |
| LN NW 13 HL | L      | PN 315             | 15        | 1/2" -14 NPT     | 14     | 36      | 21,0    | 34      | 19      | 27 |
| LN NW 16 HL | L      | PN 315             | 18        | 1/2" -14 NPT     | 16     | 40      | 23,5    | 36      | 24      | 32 |
| LN NW 20 HL | L      | PN 160             | 22        | 3/4" -14 NPT     | 16     | 44      | 27,5    | 42      | 27      | 36 |
| LN NW 25 HL | L      | PN 160             | 28        | 1" -11,5 NPT     | 25     | 47      | 30,5    | 48      | 36      | 41 |
| LN NW 32 HL | L      | PN 160             | 35        | 1.1/4" -11,5 NPT | 20     | 56      | 34,5    | 54      | 41      | 50 |
| LN NW 40 HL | L      | PN 160             | 42        | 1.1/2" -11,5 NPT | 22     | 63      | 40,0    | 61      | 50      | 60 |
| LN NW 03 HS | S      | PN 630             | 6         | 1/4" -18 NPT     | 12     | 31      | 16,0    | 26      | 12      | 17 |
| LN NW 04 HS | S      | PN 630             | 8         | 1/4" -18 NPT     | 12     | 32      | 17,0    | 27      | 14      | 19 |
| LN NW 06 HS | S      | PN 630             | 10        | 3/8" -18 NPT     | 12     | 34      | 17,5    | 28      | 17      | 22 |
| LN NW 08 HS | S      | PN 630             | 12        | 3/8" -18 NPT     | 12     | 38      | 21,5    | 28      | 17      | 24 |
| LN NW 10 HS | S      | PN 630             | 14        | 1/2" -14 NPT     | 14     | 40      | 22,0    | 34      | 19      | 27 |
| LN NW 13 HS | S      | PN 400             | 16        | 1/2" -14 NPT     | 14     | 43      | 24,5    | 36      | 24      | 30 |
| LN NW 16 HS | S      | PN 400             | 20        | 3/4" -14 NPT     | 23     | 48      | 26,5    | 42      | 27      | 36 |
| LN NW 20 HS | S      | PN 400             | 25        | 1" -11,5 NPT     | 25     | 54      | 30,0    | 48      | 36      | 46 |
| LN NW 25 HS | S      | PN 400             | 30        | 1.1/4" -11,5 NPT | 20     | 62      | 35,5    | 54      | 41      | 50 |
| LN NW 32 HS | S      | PN 315             | 38        | 1.1/2" -11,5 NPT | 26     | 72      | 41,0    | 61      | 50      | 60 |

Seriya: LL = veoma lako L = lako S = teško - PN = nominalni pritisak PB = maks. radni pritisak - Ø d2 = spoljni prečnik cevi

### Varijante proizvoda

|              |   |
|--------------|---|
| <b>LN VA</b> | Uvrtni navojni spoj, L oblik, plemeniti čelik |
| <b>XLN</b>   | Uvrtni navojni spoj, L oblik, čelik           |