

Osobine

| | |
|-------------------------------|---|
| Priključak 1 | BSP spoljni cilindrični navoj |
| Oblik zaptivke 1 | Oblik E |
| Priključak 2 | metrički spoljni cilindrični navoj |
| Oblik zaptivke 2 | 24° unutrašnji konus |
| Konstrukcija | Zglobni navojni spoj (uvrtni navojni spoj) |
| Dodatak za vrstu konstrukciju | Klizni ležaj |
| Konstrukcija | pravo |
| Obim isporuke | Nastavak (bez preklopne navrtke i reznog prstena) |
| Materijal | čelik |
| Površinska zaštita | galvanska prevlaka |



Napomena

Molimo Vas da napomene za montažu, ugradnju, opterećenje pod pritiskom i dozvoljene radne temperature nađete u tehničkim informacijama o navojnim spojevima za cevi.

Artikal

| Naziv | Seriya | Radni pritisak bar | Ø d2 (mm) | G1 | i (mm) | Ø d3 (mm) | L1 (mm) | L2 (mm) | L3 (mm) | SW (mm) | S1 | S2 |
|--------------------|--------|--------------------|-----------|--------------|--------|-----------|---------|---------|---------|---------|----|----|
| GVR NW 04 HL 1/4 | L | PN 40 | 6 | G 1/4" -19 | 12 | 19 | 40 | 21,0 | 18,0 | 19 | 12 | 14 |
| GVR NW 06 HL | L | PN 40 | 8 | G 1/4" -19 | 12 | 19 | 40 | 21,0 | 18,0 | 19 | 14 | 17 |
| GVR NW 08 HL 3/8 | L | PN 40 | 10 | G 3/8" -19 | 12 | 22 | 40 | 25,0 | 18,0 | 24 | 17 | 19 |
| GVR NW 10 HL 1/2 | L | PN 40 | 12 | G 1/2" -14 | 14 | 27 | 42 | 27,0 | 21,0 | 27 | 19 | 22 |
| GVR NW 13 HL 3/4 | L | PN 40 | 15 | G 3/4" -14 | 16 | 32 | 47 | 32,0 | 24,0 | 32 | 24 | 27 |
| GVR NW 16 HL 1 | L | PN 40 | 18 | G 1" -11 | 18 | 40 | 51 | 35,0 | 27,5 | 41 | 27 | 22 |
| GVR NW 20 HL 1 | L | PN 40 | 22 | G 1" -11 | 18 | 40 | 55 | 39,5 | 27,5 | 41 | 32 | 36 |
| GVR NW 25 HL 1 1/4 | L | PN 40 | 28 | G 1.1/4" -11 | 20 | 40 | 57 | 40,5 | 31,0 | 50 | 41 | 41 |
| GVR NW 32 HL 1 1/2 | L | PN 40 | 35 | G 1.1/2" -11 | 22 | 55 | 66 | 44,5 | 35,0 | 55 | 46 | 50 |
| GVR NW 03 HS | S | PN 100 | 6 | G 1/4" -19 | 12 | 19 | 38 | 23,0 | 18,0 | 19 | 14 | 17 |
| GVR NW 04 HS | S | PN 100 | 8 | G 1/4" -19 | 12 | 19 | 39 | 24,0 | 18,0 | 19 | 17 | 19 |
| GVR NW 06 HS | S | PN 100 | 10 | G 3/8" -19 | 12 | 22 | 43 | 26,5 | 18,0 | 24 | 19 | 22 |
| GVR NW 08 HS 1/2 | S | PN 100 | 12 | G 1/2" -14 | 14 | 27 | 45 | 28,5 | 21,0 | 27 | 22 | 24 |
| GVR NW 13 HS 3/4 | S | PN 100 | 16 | G 3/4" -14 | 16 | 32 | 52 | 33,5 | 24,0 | 32 | 27 | 30 |
| GVR NW 16 HS 1 | S | PN 100 | 20 | G 1" -11 | 18 | 40 | 60 | 38,0 | 27,5 | 41 | 32 | 36 |
| GVR NW 20 HS | S | PN 100 | 25 | G 1" -11 | 18 | 40 | 65 | 40,5 | 27,5 | 41 | 41 | 46 |
| GVR NW 25 HS 1 1/4 | S | PN 100 | 30 | G 1.1/4" -11 | 20 | 50 | 68 | 41,5 | 31,0 | 50 | 46 | 50 |
| GVR NW 32 HS 1 1/2 | S | PN 100 | 38 | G 1.1/2" -11 | 22 | 55 | 78 | 47,0 | 35,0 | 55 | 55 | 60 |

Seriya: LL = veoma lako L = lako S = teško - PN = nominalni pritisak PB = maks. radni pritisak - Ø d2 = spoljni prečnik cevi