


WF LK

Priključak za pumpu, (sa 4 otvora), ugao 90°

HANSA FLEX

Osobine

Konstrukcija	Priključak za pumpu (sa 4 otvora)
Konstrukcija	ugao 90°
Norma	DIN 3901 / 3902
Pričvršćivanje	sa metričkim kompletom zavrtnjeva
Obim isporuke	sa metričkim kompletom zavrtnjeva i O-prstenom
Materijal	temper liv GTW40
Površinska zaštita	galvanska prevlaka



Napomena

Navedeni maksimalni radni pritisak odnosi se na priрубnicu! Stvarni radni pritisak se određuje na osnovu cevi (debljina zida) kao i kvaliteta cevi!

Artikal

Naziv	Seriya	I	Ø RAD	Pritisak PB	A	LK	D	S1	S2	L	Zavrtnji 1	Zavrtnji 2	OR	
			(mm)	(mm)	(bar)	(mm)	(mm)	(mm)	(mm)	(mm)				
WF 35 LK L 10 315	L		14,0	10	315	M16x1,5	35	39	16,5	30,5	6,4	(2x) M 6 x 22	(2x) M 6 x 35	20,0 x 2,5
WF 35 LK L 12 315	L		14,0	12	315	M18x1,5	35	39	16,5	30,5	6,4	(2x) M 6 x 22	(2x) M 6 x 35	20,0 x 2,5
WF 35 LK L 15 250	L		14,0	15	250	M22x1,5	35	39	16,5	30,0	6,4	(2x) M 6 x 22	(2x) M 6 x 35	20,0 x 2,5
WF 35 LK L 18 250	L		15,0	18	250	M22x1,5	35	39	20,0	30,0	6,4	(2x) M 6 x 22	(2x) M 6 x 40	20,0 x 2,5
WF 40 LK L 15 100	L		20,0	15	100	M22x1,5	40	42	22,5	30,0	6,4	(2x) M 6 x 22	(2x) M 6 x 45	26,0 x 2,5
WF 40 LK L 18 100	L		20,0	18	100	M26x1,5	40	42	22,5	30,5	6,4	(2x) M 6 x 22	(2x) M 6 x 45	26,0 x 2,5
WF 40 LK L 22 100	L		20,0	22	100	M30x2	40	42	22,5	30,5	6,4	(2x) M 6 x 22	(2x) M 6 x 45	26,0 x 2,5
WF 40 LK L 28 100	L		20,0	28	100	M36x2	40	42	28,0	32,5	6,4	(2x) M 6 x 22	(2x) M 6 x 50	26,0 x 2,5
WF 40 LK L 35 100	L		20,0	35	100	M45x2	40	42	34,0	30,5	6,4	(2x) M 6 x 22	(2x) M 6 x 60	26,0 x 2,5
WF 55 LK L 35 100	L		26,0	35	100	M45x2	55	58	32,0	38,5	8,4	(2x) M 8 x 25	(2x) M 8 x 60	32,0 x 2,5
WF 55 LK L 42 100	L		26,0	42	100	M52x2	55	58	40,0	38,0	8,4	(2x) M 8 x 25	(2x) M 8 x 70	32,0 x 2,5
WF 35 LK S 16 315	S		15,0	16	315	M24x1,5	35	39	20,0	29,5	6,4	(2x) M 6 x 22	(2x) M 6 x 40	20,0 x 2,5
WF 35 LK S 20 315	S		15,0	20	315	M30x2	35	39	25,0	34,5	6,4	(2x) M 6 x 22	(2x) M 6 x 45	20,0 x 2,5
WF 40 LK S 20 250	S		20,0	20	250	M30x2	40	42	22,5	29,5	6,4	(2x) M 6 x 22	(2x) M 6 x 45	26,0 x 2,5
WF 55 LK S 20 250	S		18,0	20	250	M30x2	55	58	30,0	34,5	8,4	(2x) M 8 x 25	(2x) M 8 x 55	32,0 x 2,5
WF 55 LK S 25 250	S		20,0	25	250	M36x2	55	58	30,0	37,0	8,4	(2x) M 8 x 25	(2x) M 8 x 55	32,0 x 2,5
WF 55 LK S 30 250	S		26,0	30	250	M42x2	55	58	32,0	35,5	8,4	(2x) M 8 x 25	(2x) M 8 x 50	32,0 x 2,5

Seriya: LL = veoma lako L = lako S = teško - PN = nominalni pritisak PB = maks. radni pritisak - Ø RAD = spoljni prečnik cevi

Varijante proizvoda

WF LK M Priključak za pumpu, (sa 4 otvora), ugao 90°, sa kompletom zavrtnjeva, O-prstenom, navrtkom i reznim prstenom