


### Osobine

<b>Prikjučak 1 + 2</b>	metrički spoljni cilindrični navoj
<b>Oblik zaptivke 1 + 2</b>	24° unutrašnji konus
<b>Konstrukcija</b>	Pregradni navojni spoj
<b>Konstrukcija</b>	ugao 90°
<b>Norma</b>	DIN 2353 ISO 8434-1
<b>Obim isporuke</b>	Nastavak sa preklopnom navrtkom i reznim prstenom
<b>Materijal</b>	plemeniti čelik



### Napomena

Molimo Vas da napomene za montažu, ugradnju, opterećenje pod pritiskom i dozvoljene radne temperature nađete u tehničkim informacijama o navojnim spojevima za cevi.

### Artikal

Naziv	Seriya	Radni pritisak bar	Ø d2 (mm)	G1	Ø D (mm)	b (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	L5 (mm)	SW (mm)	S1	S2
SW NW 04 HL VA	L	PN 315	6	M 12 x 1,5	17	16	42	27,0	27	12,0	14	12	17	14
SW NW 06 HL VA	L	PN 315	8	M 14 x 1,5	19	16	42	27,0	29	14,0	17	12	19	17
SW NW 08 HL VA	L	PN 315	10	M 16 x 1,5	22	16	43	28,0	30	15,0	18	14	22	19
SW NW 10 HL VA	L	PN 315	12	M 18 x 1,5	24	16	44	29,0	32	17,0	20	17	24	22
SW NW 13 HL VA	L	PN 315	15	M 22 x 1,5	27	16	46	31,0	36	21,0	23	19	30	27
SW NW 16 HL VA	L	PN 315	18	M 26 x 1,5	32	16	49	32,5	40	23,5	24	24	36	32
SW NW 20 HL VA	L	PN 160	22	M 30 x 2	36	16	51	34,5	44	27,5	30	27	41	36
SW NW 25 HL VA	L	PN 160	28	M 36 x 2	42	16	52	35,5	47	30,5	34	36	46	41
SW NW 32 HL VA	L	PN 160	35	M 45 x 2	50	16	58	36,5	56	34,5	39	41	55	50
SW NW 40 HL VA	L	PN 160	42	M 52 x 2	60	16	59	36,0	63	40,0	43	50	65	60
SW NW 03 HS VA	S	PN 630	6	M 14 x 1,5	19	16	44	29,0	31	16,0	17	12	19	17
SW NW 04 HS VA	S	PN 630	8	M 16 x 1,5	22	16	44	29,0	32	17,0	18	14	22	19
SW NW 06 HS VA	S	PN 630	10	M 18 x 1,5	24	16	46	29,5	34	17,5	20	17	24	22
SW NW 08 HS VA	S	PN 630	12	M 20 x 1,5	27	16	47	30,5	38	21,5	21	17	27	24
SW NW 10 HS VA	S	PN 630	14	M 22 x 1,5	27	16	50	32,0	40	22,0	23	19	30	27
SW NW 13 HS VA	S	PN 400	16	M 24 x 1,5	30	16	50	31,5	43	24,5	24	24	32	30
SW NW 16 HS VA	S	PN 400	20	M 30 x 2	36	16	55	33,5	48	26,5	30	27	41	36
SW NW 20 HS VA	S	PN 400	25	M 36 x 2	42	16	59	35,0	54	30,0	34	36	46	46
SW NW 25 HS VA	S	PN 400	30	M 42 x 2	50	16	64	37,5	62	35,5	39	41	50	50
SW NW 32 HS VA	S	PN 315	38	M 52 x 2	60	16	68	37,0	72	41,0	43	50	65	60

Seriya: LL = veoma lako L = lako S = teško - PN = nominalni pritisak PB = maks. radni pritisak - Ø d2 = spoljni prečnik cevi

### Varijante proizvoda

<b>SW</b>	Pregradni navojni spoj, ugao 90°, čelik
<b>SW MG</b>	Pregradni navojni spoj, ugao 90°, Mesing
<b>XSW VA</b>	Pregradni navojni spoj, ugao 90°, plemeniti čelik