

### Osobine

<b>Priključak 1</b>	BSP spoljni cilindrični navoj
<b>Oblik zaptivke 1</b>	oblik G
<b>Priključak 2</b>	metrički spoljni cilindrični navoj
<b>Oblik zaptivke 2</b>	24° unutrašnji konus
<b>Konstrukcija</b>	Uvrtni navojni spoj, podesiv po pravcima
<b>Konstrukcija</b>	ugao 90°
<b>Obim isporuke</b>	Nastavak (bez preklopne navrtke i reznog prstena)
<b>Materijal</b>	čelik
<b>Površinska zaštita</b>	galvanska prevlaka



### Napomena

Molimo Vas da napomene za montažu, ugradnju, opterećenje pod pritiskom i dozvoljene radne temperature nađete u tehničkim informacijama o navojnim spojevima za cevi.

### Artikal

Naziv	Seriya	Radni pritisak bar	Ø d2 (mm)	G1	G2	i (mm)	L4 (mm)	L5 (mm)	L7 (mm)	SW (mm)	S1	OR
XEWOR NW 04 HL	L	PN 250	6	G 1/8" -28	M 12 x 1,5	8	12,0	21,5	19	12	14	8,0 x 1,5
XEWOR NW 06 HL	L	PN 250	8	G 1/4" -19	M 14 x 1,5	12	14,0	26,0	21	14	19	10,0 x 2,0
XEWOR NW 06 HL 3/8	L	PN 250	8	G 3/8" -19	M 14 x 1,5	12	17,0	28,5	24	17	22	14,0 x 2,5
XEWOR NW 08 HL	L	PN 250	10	G 1/4" -19	M 16 x 1,5	12	15,0	26,0	22	14	19	10,0 x 2,0
XEWOR NW 10 HL	L	PN 250	12	G 3/8" -19	M 18 x 1,5	12	17,0	28,5	24	17	22	14,0 x 2,5
XEWOR NW 13 HL	L	PN 250	15	G 1/2" -14	M 22 x 1,5	14	21,0	33,5	28	19	27	18,0 x 3,0
XEWOR NW 16 HL	L	PN 160	18	G 1/2" -14	M 26 x 1,5	14	23,5	36,5	31	24	27	18,0 x 3,0
XEWOR NW 20 HL	L	PN 160	22	G 3/4" -14	M 30 x 2	16	27,5	41,0	35	27	32	23,5 x 3,0
XEWOR NW 25 HL	L	PN 100	28	G 1" -11	M 36 x 2	18	30,5	45,0	38	36	41	29,0 x 3,5
XEWOR NW 32 HL	L	PN 100	35	G 1.1/4" -11	M 45 x 2	20	34,5	50,0	45	41	50	38,0 x 3,5
XEWOR NW 40 HL	L	PN 100	42	G 1.1/2" -11	M 52 x 2	22	40,0	56,0	51	50	55	44,0 x 3,5
XEWOR NW 03 HS	S	PN 630	6	G 1/4" -19	M 14 x 1,5	12	15,0	26,0	22	12	19	10,0 x 2,0
XEWOR NW 04 HS	S	PN 630	8	G 1/4" -19	M 16 x 1,5	12	17,0	27,0	24	14	19	10,0 x 2,0
XEWOR NW 06 HS	S	PN 630	10	G 3/8" -19	M 18 x 1,5	12	17,5	28,5	25	17	22	14,0 x 2,5
XEWOR NW 08 HS	S	PN 630	12	G 3/8" -19	M 20 x 1,5	12	21,5	32,5	29	19	22	14,0 x 2,5
XEWOR NW 10 HS	S	PN 630	14	G 1/2" -14	M 22 x 1,5	14	22,0	33,5	30	19	27	18,0 x 3,0
XEWOR NW 13 HS	S	PN 400	16	G 1/2" -14	M 24 x 1,5	14	24,5	36,5	33	24	27	18,0 x 3,0
XEWOR NW 16 HS	S	PN 400	20	G 3/4" -14	M 30 x 2	16	26,5	41,0	39	27	32	23,5 x 3,0
XEWOR NW 20 HS	S	PN 400	25	G 1" -11	M 36 x 2	18	30,0	45,0	42	36	41	29,0 x 3,5
XEWOR NW 25 HS	S	PN 250	30	G 1.1/4" -11	M 42 x 2	20	35,5	50,0	49	41	50	38,0 x 3,5
XEWOR NW 32 HS	S	PN 250	38	G 1.1/2" -11	M 52 x 2	22	41,0	56,0	57	50	55	44,0 x 3,5

PN = nominalni pritisak PB = maks. radni pritisak - Serija: LL = veoma lako L = lako S = teško - Ø d2 = spoljni prečnik cevi

### Varijante proizvoda

**EWOR** Uvrtni navojni spoj, ugao 90°, Nastavak sa preklopnom navrtkom i reznim prstenom