

Osobine

Priključak 1	BSP spoljni cilindrični navoj
Oblik zaptivke 1	O-prsten i komorni prsten
Priključak 2	metrički spoljni cilindrični navoj
Oblik zaptivke 2	24° unutrašnji konus
Konstrukcija	Uvrtni navojni spoj, podesiv po pravcima
Konstrukcija	ugao 90°
Obim isporuke	Nastavak (bez preklopne navrtke i reznog prstena)
Materijal	čelik
Površinska zaštita	galvanska prevlaka



Napomena

Molimo Vas da napomene za montažu, ugradnju, opterećenje pod pritiskom i dozvoljene radne temperature nađete u tehničkim informacijama o navojnim spojevima za cevi.

Artikal

Naziv	Seriya	Radni pritisak bar	Ø d2 (mm)	G1	G2	i (mm)	L4 (mm)	L5 (mm)	L7 (mm)	SW (mm)	S1	OR
XEWORK 04 LL	LL	PN 250	4	G 1/8" -28	M 8 x 1	7,1	11,3	20	15	11	14	7,65 x 1,78
XEWORK 06 LL	LL	PN 250	6	G 1/8" -28	M 10 x 1	7,1	11,3	20	15	11	14	7,65 x 1,78
XEWORK NW 04 HL	L	PN 315	6	G 1/8" -28	M 12 x 1,5	7,0	14,0	19	21	14	14	7,65 x 1,78
XEWORK NW 06 HL	L	PN 315	8	G 1/4" -19	M 14 x 1,5	9,0	16,0	23	23	14	19	10,78 x 2,62
XEWORK NW 08 HL	L	PN 315	10	G 1/4" -19	M 16 x 1,5	9,0	17,0	25	24	19	19	10,77 x 2,62
XEWORK NW 10 HL	L	PN 250	12	G 3/8" -19	M 18 x 1,5	9,0	19,0	28	26	19	22	13,94 x 2,62
XEWORK NW 13 HL	L	PN 250	15	G 1/2" -14	M 22 x 1,5	13,0	21,0	30	28	22	27	17,86 x 2,62
XEWORK NW 16 HL	L	PN 250	18	G 1/2" -14	M 26 x 1,5	13,0	24,0	36	31	27	27	17,86 x 2,62
XEWORK NW 20 HL	L	PN 160	22	G 3/4" -14	M 30 x 2	13,0	28,0	36	35	30	36	23,47 x 2,62
XEWORK NW 25 HL	L	PN 160	28	G 1" -11	M 36 x 2	15,0	31,0	44	38	36	41	29,74 x 3,53
XEWORK NW 32 HL	L	PN 160	35	G 1.1/4" -11	M 45 x 2	15,0	38,0	50	48	50	50	37,69 x 3,53
XEWORK NW 40 HL	L	PN 160	42	G 1.1/2" -11	M 52 x 2	15,0	38,0	52	49	50	55	44,04 x 3,53
XEWORK NW 03 HS	S	PN 315	6	G 1/4" -19	M 14 x 1,5	9,0	15,0	23	22	14	19	10,77 x 2,62
XEWORK NW 04 HS	S	PN 315	8	G 1/4" -19	M 16 x 1,5	9,0	17,0	27	24	19	19	10,77 x 2,62
XEWORK NW 06 HS	S	PN 250	10	G 3/8" -19	M 18 x 1,5	9,0	18,0	29	25	19	22	13,94 x 2,62
XEWORK NW 08 HS	S	PN 250	12	G 3/8" -19	M 20 x 1,5	9,0	22,0	29	29	22	22	13,94 x 2,62
XEWORK NW 10 HS	S	PN 250	14	G 1/2" -14	M 22 x 1,5	13,0	25,0	36	33	27	27	18,00 x 3,00
XEWORK NW 13 HS	S	PN 250	16	G 1/2" -14	M 24 x 1,5	13,0	25,0	36	33	27	27	17,86 x 2,62
XEWORK NW 16 HS	S	PN 250	20	G 3/4" -14	M 30 x 2	12,0	28,0	39	38	30	36	23,47 x 2,62
XEWORK NW 20 HS	S	PN 250	25	G 1" -11	M 36 x 2	14,0	30,0	44	42	36	41	29,74 x 3,53
XEWORK NW 25 HS	S	PN 160	30	G 1.1/4" -11	M 42 x 2	15,0	36,0	49	49	50	50	37,69 x 3,53
XEWORK NW 32 HS	S	PN 160	38	G 1.1/2" -11	M 52 x 2	15,0	34,0	55	50	50	55	44,04 x 3,53

Seriya: LL = veoma lako L = lako S = teško - PN = nominalni pritisak PB = maks. radni pritisak - Ø d2 = spoljni prečnik cevi

Varijante proizvoda

EWOR Uvrtni navojni spoj, ugao 90°, Nastavak sa preklopnom navrtkom i reznim prstenom