


### Osobine

<b>Priključak 1</b>	BSP spoljni cilindrični navoj
<b>Oblik zaptivke 1</b>	O-prsten i komorni prsten
<b>Priključak 2</b>	metrički spoljni cilindrični navoj
<b>Oblik zaptivke 2</b>	24° unutrašnji konus
<b>Konstrukcija</b>	Uvrtni navojni spoj, podesiv po pravcima
<b>Konstrukcija</b>	ugao 90°
<b>Obim isporuke</b>	Nastavak (bez preklopne navrtke i reznog prstena)
<b>Materijal</b>	čelik
<b>Površinska zaštita</b>	galvanska prevlaka



### Napomena

Molimo Vas da napomene za montažu, ugradnju, opterećenje pod pritiskom i dozvoljene radne temperature nađete u tehničkim informacijama o navojnim spojevima za cevi.

### Artikal

Naziv	Seriya	Radni pritisak bar	Ø d2 (mm)	G1	G2	i (mm)	L4 (mm)	L5 (mm)	L7 (mm)	SW (mm)	S1	OR
<b>XEWORK 04 LL</b>	LL	PN 250	4	G 1/8" -28	M 8 x 1	7,1	11,3	20	15	11	14	7,65 x 1,78
<b>XEWORK 06 LL</b>	LL	PN 250	6	G 1/8" -28	M 10 x 1	7,1	11,3	20	15	11	14	7,65 x 1,78
<b>XEWORK NW 04 HL</b>	L	PN 315	6	G 1/8" -28	M 12 x 1,5	7,0	14,0	19	21	14	14	7,65 x 1,78
<b>XEWORK NW 06 HL</b>	L	PN 315	8	G 1/4" -19	M 14 x 1,5	9,0	16,0	23	23	14	19	10,78 x 2,62
<b>XEWORK NW 08 HL</b>	L	PN 315	10	G 1/4" -19	M 16 x 1,5	9,0	17,0	25	24	19	19	10,77 x 2,62
<b>XEWORK NW 10 HL</b>	L	PN 250	12	G 3/8" -19	M 18 x 1,5	9,0	19,0	28	26	19	22	13,94 x 2,62
<b>XEWORK NW 13 HL</b>	L	PN 250	15	G 1/2" -14	M 22 x 1,5	13,0	21,0	30	28	22	27	17,86 x 2,62
<b>XEWORK NW 16 HL</b>	L	PN 250	18	G 1/2" -14	M 26 x 1,5	13,0	24,0	36	31	27	27	17,86 x 2,62
<b>XEWORK NW 20 HL</b>	L	PN 160	22	G 3/4" -14	M 30 x 2	13,0	28,0	36	35	30	36	23,47 x 2,62
<b>XEWORK NW 25 HL</b>	L	PN 160	28	G 1" -11	M 36 x 2	15,0	31,0	44	38	36	41	29,74 x 3,53
<b>XEWORK NW 32 HL</b>	L	PN 160	35	G 1.1/4" -11	M 45 x 2	15,0	38,0	50	48	50	50	37,69 x 3,53
<b>XEWORK NW 40 HL</b>	L	PN 160	42	G 1.1/2" -11	M 52 x 2	15,0	38,0	52	49	50	55	44,04 x 3,53
<b>XEWORK NW 03 HS</b>	S	PN 315	6	G 1/4" -19	M 14 x 1,5	9,0	15,0	23	22	14	19	10,77 x 2,62
<b>XEWORK NW 04 HS</b>	S	PN 315	8	G 1/4" -19	M 16 x 1,5	9,0	17,0	27	24	19	19	10,77 x 2,62
<b>XEWORK NW 06 HS</b>	S	PN 250	10	G 3/8" -19	M 18 x 1,5	9,0	18,0	29	25	19	22	13,94 x 2,62
<b>XEWORK NW 08 HS</b>	S	PN 250	12	G 3/8" -19	M 20 x 1,5	9,0	22,0	29	29	22	22	13,94 x 2,62
<b>XEWORK NW 10 HS</b>	S	PN 250	14	G 1/2" -14	M 22 x 1,5	13,0	25,0	36	33	27	27	18,00 x 3,00
<b>XEWORK NW 13 HS</b>	S	PN 250	16	G 1/2" -14	M 24 x 1,5	13,0	25,0	36	33	27	27	17,86 x 2,62
<b>XEWORK NW 16 HS</b>	S	PN 250	20	G 3/4" -14	M 30 x 2	12,0	28,0	39	38	30	36	23,47 x 2,62
<b>XEWORK NW 20 HS</b>	S	PN 250	25	G 1" -11	M 36 x 2	14,0	30,0	44	42	36	41	29,74 x 3,53
<b>XEWORK NW 25 HS</b>	S	PN 160	30	G 1.1/4" -11	M 42 x 2	15,0	36,0	49	49	50	50	37,69 x 3,53
<b>XEWORK NW 32 HS</b>	S	PN 160	38	G 1.1/2" -11	M 52 x 2	15,0	34,0	55	50	50	55	44,04 x 3,53

Seriya: LL = veoma lako L = lako S = teško - PN = nominalni pritisak PB = maks. radni pritisak - Ø d2 = spoljni prečnik cevi

### Varijante proizvoda

**EWOR** Uvrtni navojni spoj, ugao 90°, Nastavak sa preklopnom navrtkom i reznim prstenom