

XEWORK 45

Uvrtni navojni spoj, ugao 45°

HANSA FLEX

Osobine

Priključak 1	BSP spoljni cilindrični navoj
Oblik zaptivke 1	O-prsten i komorni prsten
Priključak 2	metrički spoljni cilindrični navoj
Oblik zaptivke 2	24° unutrašnji konus
Konstrukcija	Uvrtni navojni spoj, podesiv po pravcima
Konstrukcija	ugao 45°
Obim isporuke	Nastavak (bez preklopne navrtke i reznog prstena)
Materijal	čelik
Površinska zaštita	galvanska prevlaka



Napomena

Molimo Vas da napomene za montažu, ugradnju, opterećenje pod pritiskom i dozvoljene radne temperature nađete u tehničkim informacijama o navojnim spojevima za cevi.

Artikal

Naziv	Seriya	Radni pritisak bar	Ø d2 (mm)	G1	G2	i (mm)	L4 (mm)	L5 (mm)	L7 (mm)	SW (mm)	S1	OR
XEWORK 45 NW 04 HL	L	PN 315	6	G 1/8" -28	M 12 x 1,5	7	9	21	16	14	14	7,65 x 1,78
XEWORK 45 NW 06 HL	L	PN 315	8	G 1/4" -19	M 14 x 1,5	9	12	20	19	14	19	10,78 x 2,62
XEWORK 45 NW 08 HL	L	PN 315	10	G 1/4" -19	M 16 x 1,5	9	12	25	19	19	19	10,78 x 2,62
XEWORK 45 NW 10 HL	L	PN 250	12	G 3/8" -19	M 18 x 1,5	9	14	28	21	19	22	13,94 x 2,62
XEWORK 45 NW 13 HL	L	PN 250	15	G 1/2" -14	M 22 x 1,5	13	17	26	24	22	27	17,86 x 2,62
XEWORK 45 NW 16 HL	L	PN 250	18	G 1/2" -14	M 26 x 1,5	13	17	32	24	27	27	17,86 x 2,62
XEWORK 45 NW 20 HL	L	PN 160	22	G 3/4" -14	M 30 x 2	13	19	37	26	30	36	23,47 x 2,62
XEWORK 45 NW 20 HL 27	L	PN 160	22	G 3/4" -14	M 27 x 2	13	19	37	26	30	36	23,47 x 2,62
XEWORK 45 NW 25 HL	L	PN 160	28	G 1" -11	M 36 x 2	15	23	37	31	36	41	29,74 x 3,53
XEWORK 45 NW 32 HL	L	PN 160	35	G 1.1/4" -11	M 45 x 2	15	27	39	37	50	50	37,69 x 3,53
XEWORK 45 NW 40 HL	L	PN 160	42	G 1.1/2" -11	M 52 x 2	15	26	39	37	50	55	44,04 x 3,53
XEWORK 45 NW 03 HS	S	PN 315	6	G 1/4" -19	M 14 x 1,5	9	9	19	16	14	19	10,78 x 2,62
XEWORK 45 NW 04 HS	S	PN 315	8	G 1/4" -19	M 16 x 1,5	9	12	23	19	19	19	10,78 x 2,62
XEWORK 45 NW 06 HS	S	PN 250	10	G 3/8" -19	M 18 x 1,5	9	13	25	21	19	22	13,94 x 2,62
XEWORK 45 NW 08 HS	S	PN 250	12	G 3/8" -19	M 20 x 1,5	9	17	25	24	22	22	13,94 x 2,62
XEWORK 45 NW 10 HS	S	PN 250	14	G 1/2" -14	M 22 x 1,5	13	16	31	24	27	27	17,86 x 2,62
XEWORK 45 NW 13 HS	S	PN 250	16	G 1/2" -14	M 24 x 1,5	13	16	31	24	27	27	17,86 x 2,62
XEWORK 45 NW 16 HS	S	PN 250	20	G 3/4" -14	M 30 x 2	12	16	34	27	30	36	23,47 x 2,62
XEWORK 45 NW 20 HS	S	PN 250	25	G 1" -11	M 36 x 2	14	19	37	31	36	41	29,74 x 3,53
XEWORK 45 NW 25 HS	S	PN 160	30	G 1.1/4" -11	M 42 x 2	15	24	38	37	50	50	37,69 x 3,53
XEWORK 45 NW 32 HS	S	PN 160	38	G 1.1/2" -11	M 52 x 2	15	21	38	37	50	55	44,04 x 3,53

Seriya: LL = veoma lako L = lako S = teško - PN = nominalni pritisak PB = maks. radni pritisak - Ø d2 = spoljni prečnik cevi

Varijante proizvoda

EWOK 45 Uvrtni navojni spoj, ugao 45°, Nastavak sa preklopnom navrtkom i reznim prstenom