


XWMK VA

Uvrtni navojni spoj, ugao 90°

HANSA FLEX

Osobine

Priključak 1	metrički spoljni konusni navoj
Oblik zaptivke 1	zaptivanje preko navoja
Priključak 2	metrički spoljni cilindrični navoj
Oblik zaptivke 2	24° unutrašnji konus
Konstrukcija	Uvrtni navojni spoj
Konstrukcija	ugao 90°
Norma	DIN 2353 ISO 8434-1
Obim isporuke	Nastavak (bez preklopne navrtke i reznog prstena)
Materijal	plemeniti čelik



Napomena

Molimo Vas da napomene za montažu, ugradnju, opterećenje pod pritiskom i dozvoljene radne temperature nađete u tehničkim informacijama o navojnim spojevima za cevi.

Artikal

Naziv	Seriya	Radni pritisak bar	Ø d2 (mm)	G	i (mm)	L4 (mm)	L5 (mm)	L7 (mm)	SW (mm)
XWM 04 LL 6 VA	LL	PN 100	4	M 6 x 1 K	8,0	11,0	17	15	9
XWM 04 LL VA	LL	PN 100	4	M 8 x 1 K	8,0	11,0	17	15	9
XWM 04 LL 10 VA	LL	PN 100	4	M 10 x 1 K	8,0	11,0	17	15	9
XWM 06 LL 6 VA	LL	PN 100	6	M 6 x 1 K	7,0	9,5	17	15	9
XWM 06 LL 8 VA	LL	PN 100	6	M 8 x 1 K	8,0	9,5	17	15	9
XWM 06 LL VA	LL	PN 100	6	M 10 x 1 K	9,0	9,5	17	15	9
XWM 08 LL 6 VA	LL	PN 100	8	M 6 x 1 K	8,0	11,5	20	17	12
XWM 08 LL 8 VA	LL	PN 100	8	M 8 x 1 K	8,0	11,5	20	17	12
XWM 08 LL VA	LL	PN 100	8	M 10 x 1 K	10,0	11,5	20	17	12
XWM NW 04 HL VA	L	PN 315	6	M 10 x 1 K	8,0	12,0	20	19	12
XWM NW 06 HL VA	L	PN 315	8	M 12 x 1,5 K	12,0	14,0	26	21	12
XWM NW 08 HL 12 VA	L	PN 315	10	M 12 x 1,5 K	12,0	15,0	27	22	14
XWM NW 08 HL VA	L	PN 315	10	M 14 x 1,5 K	11,5	15,0	27	22	14
XWM NW 10 HL VA	L	PN 315	12	M 16 x 1,5 K	11,5	17,0	28	24	17
XWM NW 13 HL VA	L	PN 315	15	M 18 x 1,5 K	13,5	21,0	32	28	19
XWM NW 16 HL VA	L	PN 315	18	M 22 x 1,5 K	15,0	23,5	36	31	24
XWM NW 03 HS VA	S	PN 400	6	M 12 x 1,5 K	12,0	16,0	26	23	12
XWM NW 04 HS VA	S	PN 400	8	M 14 x 1,5 K	12,0	17,0	27	24	14
XWM NW 06 HS VA	S	PN 400	10	M 16 x 1,5 K	12,0	17,5	28	25	17
XWM NW 08 HS VA	S	PN 400	12	M 18 x 1,5 K	12,0	21,5	28	29	17
XWM NW 10 HS VA	S	PN 400	14	M 20 x 1,5 K	14,0	22,0	32	30	19
XWM NW 13 HS VA	S	PN 400	16	M 22 x 1,5 K	14,0	24,5	32	33	24

Seriya: LL = veoma lako L = lako S = teško – PN = nominalni pritisak PB = maks. radni pritisak – Ø d2 = spoljni prečnik cevi

Varijante proizvoda

XWMK	Uvrtni navojni spoj, ugao 90°, čelik
WMK VA	Uvrtni navojni spoj, ugao 90°, plemeniti čelik