


Osobine

| | |
|--------------------|---------------------------------------------------|
| Priključak 1 | NPT spoljni navoj |
| Oblik zaptivke 1 | zaptivanje preko navoja |
| Priključak 2 | metrički spoljni cilindrični navoj |
| Oblik zaptivke 2 | 24° unutrašnji konus |
| Konstrukcija | Uvrtni navojni spoj |
| Konstrukcija | ugao 90° |
| Norma | DIN 2353 ISO 8434-1 |
| Obim isporuke | Nastavak (bez preklopne navrtke i reznog prstena) |
| Materijal | čelik |
| Površinska zaštita | galvanska prevlaka |



Napomena

Molimo Vas da napomene za montažu, ugradnju, opterećenje pod pritiskom i dozvoljene radne temperature nađete u tehničkim informacijama o navojnim spojevima za cevi.

Artikal

| Naziv | Seriya | Radni pritisak bar | Cev spolja Ø (mm) | G | i (mm) | L4 (mm) | L5 (mm) | L7 (mm) | SW (mm) |
|------------------|--------|--------------------|-------------------|------------------|--------|---------|---------|---------|---------|
| XWN 04 LL | LL | PN 100 | 4 | 1/8" -27 NPT | 8,0 | 11,0 | 17 | 15,0 | 9 |
| XWN 05 LL | LL | PN 100 | 5 | 1/8" -27 NPT | 8,0 | 11,0 | 17 | 15,0 | 9 |
| XWN 06 LL | LL | PN 100 | 6 | 1/8" -27 NPT | 8,0 | 9,5 | 17 | 15,0 | 9 |
| XWN 08 LL | LL | PN 100 | 8 | 1/8" -27 NPT | 10,0 | 11,5 | 20 | 17,0 | 12 |
| XWN NW 04 HL | L | PN 315 | 6 | 1/8" -27 NPT | 10,0 | 12,0 | 20 | 19,0 | 12 |
| XWN NW 04 HL 1/4 | L | PN 315 | 6 | 1/4" -18 NPT | 12,0 | 14,0 | 26 | 21,0 | 12 |
| XWN NW 04 HL 1/2 | L | PN 315 | 6 | 1/2" -14 NPT | 17,0 | 23,0 | 34 | 30,0 | 19 |
| XWN NW 06 HL | L | PN 315 | 8 | 1/4" -18 NPT | 12,0 | 14,0 | 26 | 21,0 | 12 |
| XWN NW 06 HL 3/8 | L | PN 315 | 8 | 3/8" -18 NPT | 15,2 | 11,5 | 20 | 18,5 | 12 |
| XWN NW 06 HL 1/2 | L | PN 315 | 8 | 1/2" -14 NPT | 17,5 | 15,0 | 26 | 22,0 | 12 |
| XWN NW 08 HL | L | PN 315 | 10 | 1/4" -18 NPT | 14,0 | 15,0 | 27 | 22,0 | 14 |
| XWN NW 08 HL 3/8 | L | PN 315 | 10 | 3/8" -18 NPT | 15,2 | 15,0 | 27 | 22,0 | 14 |
| XWN NW 10 HL | L | PN 315 | 12 | 3/8" -18 NPT | 12,5 | 17,0 | 28 | 24,0 | 17 |
| XWN NW 10 HL 1/4 | L | PN 315 | 12 | 1/4" -18 NPT | 14,0 | 17,0 | 28 | 24,0 | 17 |
| XWN NW 10 HL 1/2 | L | PN 315 | 12 | 1/2" -14 NPT | 19,0 | 23,0 | 34 | 30,0 | 19 |
| XWN NW 13 HL | L | PN 315 | 15 | 1/2" -14 NPT | 18,5 | 21,0 | 34 | 28,0 | 19 |
| XWN NW 13 HL 3/8 | L | PN 315 | 15 | 3/8" -18 NPT | 13,0 | 21,0 | 34 | 28,0 | 19 |
| XWN NW 16 HL | L | PN 315 | 18 | 1/2" -14 NPT | 20,0 | 23,5 | 36 | 31,0 | 24 |
| XWN NW 16 HL 3/4 | L | PN 315 | 18 | 3/4" -14 NPT | 18,5 | 23,5 | 40 | 31,0 | 24 |
| XWN NW 20 HL | L | PN 160 | 22 | 3/4" -14 NPT | 18,5 | 27,5 | 42 | 35,0 | 27 |
| XWN NW 25 HL | L | PN 160 | 28 | 1" -11,5 NPT | 24,0 | 30,5 | 48 | 38,0 | 36 |
| XWN NW 32 HL | L | PN 160 | 35 | 1.1/4" -11,5 NPT | 25,5 | 34,5 | 54 | 45,0 | 41 |
| XWN NW 40 HL | L | PN 160 | 42 | 1.1/2" -11,5 NPT | 26,0 | 40,0 | 61 | 51,0 | 50 |
| XWN NW 03 HS | S | PN 630 | 6 | 1/4" -18 NPT | 12,0 | 16,0 | 26 | 23,0 | 12 |
| XWN NW 04 HS | S | PN 630 | 8 | 1/4" -18 NPT | 15,0 | 17,0 | 27 | 24,0 | 14 |
| XWN NW 06 HS | S | PN 630 | 10 | 3/8" -18 NPT | 12,0 | 17,5 | 28 | 25,0 | 17 |
| XWN NW 08 HS | S | PN 630 | 12 | 3/8" -18 NPT | 12,5 | 21,5 | 28 | 29,0 | 17 |
| XWN NW 10 HS | S | PN 630 | 14 | 1/2" -14 NPT | 18,0 | 22,0 | 34 | 30,0 | 19 |
| XWN NW 13 HS | S | PN 400 | 16 | 1/2" -14 NPT | 19,0 | 24,5 | 36 | 33,0 | 24 |
| XWN NW 13 HS 3/4 | S | PN 400 | 16 | 3/4" -14 NPT | 20,0 | 24,5 | 40 | 33,0 | 24 |
| XWN NW 16 HS | S | PN 400 | 20 | 3/4" -14 NPT | 20,0 | 26,6 | 42 | 37,0 | 27 |
| XWN NW 20 HS | S | PN 400 | 25 | 1" -11,5 NPT | 24,0 | 30,0 | 48 | 42,0 | 36 |
| XWN NW 25 HS | S | PN 400 | 30 | 1.1/4" -11,5 NPT | 25,5 | 35,5 | 54 | 49,0 | 41 |
| XWN NW 32 HS | S | PN 315 | 38 | 1.1/2" -11,5 NPT | 26,0 | 41,0 | 61 | 57,0 | 50 |

Seriya: LL = veoma lako L = lako S = teško - PN = nominalni pritisak PB = maks. radni pritisak - Ø d2 = spoljni prečnik cevi

Varijante proizvoda

| | |
|--------|------------------------------------------------|
| XWN VA | Uvrtni navojni spoj, ugao 90°, plemeniti čelik |
| WN | Uvrtni navojni spoj, ugao 90°, čelik |