


# TR WGE

Cev od plastike od PA 12, mekana

**HANSA FLEX**

## Osobine

<b>Oblast primene</b>	Upravljački vodovi u hidraulici i pneumatici Tehnika vozila Laboratorija i prehrambena industrija
<b>Posebne karakteristike</b>	postojanost na temperaturu i vremenske uticaje mala težina
<b>Pogled iznutra</b>	poliamid
<b>Umetak</b>	bez
<b>spoljni izgled</b>	poliamid
<b>Boja</b>	žuta
<b>Temperatura min.</b>	-60 °C
<b>Temperatura max.</b>	100 °C
<b>Temperaturni opseg</b>	Vršna temperatura do 120°C
<b>Mediji</b>	mineralno ulje Mast Pogonski materijali postojano na vodnjikave kiseline, razređene baze i soli



## Napomena

Od 20 °C potrebno je obratiti pažnju na faktor smanjivanja pritiska.<br>(maks. radni pritisak = radni pritisak x faktor).<br>

Temp.: 20°C / 30°C / 40°C / 50°C / 60°C / 70°C / 80°C / 90°C / 100°C / 110°C / 120°C

<br>Faktor: 1,00 / 0,83 / 0,72 / 0,64 / 0,57 / 0,52 / 0,47 / 0,44 / 0,36 / 0,32 / 0,28

## Artikal

Naziv	Unutrašnji-Ø (mm)	Spoljni-Ø (mm)	Debljina zida (mm)	BD* pri 20°C (bar)	min. radijus savijanja (mm)
TR 04-0.5 WGE	3,0	4,0	0,50	19,0	20
TR 04-0.65 WGE	2,7	4,0	0,65	26,0	20
TR 04-1 WGE	2,0	4,0	1,00	45,0	20
TR 05-0.85 WGE	3,3	5,0	0,85	28,0	25
TR 05-1 WGE	3,0	5,0	1,00	34,0	25
TR 06-1 WGE	4,0	6,0	1,00	27,0	30
TR 08-1 WGE	6,0	8,0	1,00	19,0	40
TR 08-1.25 WGE	5,5	8,0	1,25	26,0	40
TR 08-1.5 WGE	5,0	8,0	1,50	31,0	40
TR 10-1 WGE	8,0	10,0	1,00	15,0	60
TR 10-1.25 WGE	7,5	10,0	1,25	19,0	60
TR 10-1.5 WGE	7,0	10,0	1,50	23,0	50
TR 10-2 WGE	6,0	10,0	2,00	34,0	50
TR 12-1 WGE	10,0	12,0	1,00	12,0	60
TR 12-1.5 WGE	9,0	12,0	1,50	19,0	60
TR 12.5-1.25 WGE	10,0	12,5	1,25	15,0	75
TR 12-2 WGE	8,0	12,0	2,00	27,0	60
TR 14-1.5 WGE	11,0	14,0	1,50	16,0	80
TR 14-2 WGE	10,0	14,0	2,00	22,0	75
TR 15-1.5 WGE	12,0	15,0	1,50	15,0	90
TR 16-2 WGE	12,0	16,0	2,00	19,0	95
TR 18-2 WGE	14,0	18,0	2,00	16,0	100
TR 20-2 WGE	16,0	20,0	2,00	14,0	120
TR 22-2 WGE	18,0	22,0	2,00	13,0	150
TR 25-2.5 WGE	20,0	25,0	2,50	14,0	150
TR 28-2.5 WGE	23,0	28,0	2,50	13,0	150
TR 30-2.5 WGE	25,0	30,0	2,50	8,0	260

BD = radni pritisak

## Varijante proizvoda

TR WB	Cev od plastike od PA 12, mekana, plava
TR WR	Cev od plastike od PA 12, mekana, crvena
TR WS	Cev od plastike od PA 12, mekana, crna
TR WT	Cev od plastike od PA 12, mekana, transparentno