

### Osobine

<b>Oblast primene</b>	Upravljački vodovi u hidraulici i pneumatici Tehnika vozila Laboratorija i prehrambena industrija
<b>Posebne karakteristike</b>	postojanost na temperaturu i vremenske uticaje mala težina
<b>Pogled iznutra</b>	poliamid
<b>Umetak</b>	bez
<b>spoljni izgled</b>	poliamid
<b>Boja</b>	crvena
<b>Temperatura min.</b>	-60 °C
<b>Temperatura max.</b>	100 °C
<b>Temperaturni opseg</b>	Vršna temperatura do 120°C
<b>Mediji</b>	mineralno ulje Mast Pogonski materijali postojano na vodnjikave kiseline, razređene baze i soli



### Napomena

Od 20 °C potrebno je obratiti pažnju na faktor smanjivanja pritiska.<br>(maks. radni pritisak = radni pritisak x faktor).<br>

Temp.: 20°C / 30°C / 40°C / 50°C / 60°C / 70°C / 80°C / 90°C / 100°C / 110°C / 120°C

<br>Faktor: 1,00 / 0,83 / 0,72 / 0,64 / 0,57 / 0,52 / 0,47 / 0,44 / 0,36 / 0,32 / 0,28

### Artikal

Naziv	Unutrašnji-Ø (mm)	Spoljni-Ø (mm)	Debljina zida (mm)	BD* pri 20°C (bar)	min. radijus savijanja (mm)
TR 04-0.5 WR	3,0	4,0	0,50	19,0	20
TR 04-0.65 WR	2,7	4,0	0,65	26,0	20
TR 04-1 WR	2,0	4,0	1,00	45,0	20
TR 05-0.85 WR	3,3	5,0	0,85	28,0	25
TR 05-1 WR	3,0	5,0	1,00	34,0	25
TR 06-1 WR	4,0	6,0	1,00	27,0	30
TR 08-1 WR	6,0	8,0	1,00	19,0	40
TR 08-1.25 WR	5,5	8,0	1,25	26,0	40
TR 08-1.5 WR	5,0	8,0	1,50	31,0	40
TR 10-1.5 WR	7,0	10,0	1,50	23,0	50
TR 10-1.25 WR	7,5	10,0	1,25	19,0	60
TR 10-1 WR	8,0	10,0	1,00	15,0	60
TR 10-2 WR	6,0	10,0	2,00	34,0	50
TR 12-1 WR	10,0	12,0	1,00	12,0	55
TR 12-1.5 WR	9,0	12,0	1,50	19,0	60
TR 12.5-1.25 WR	10,0	12,5	1,25	15,0	75
TR 12-2 WR	8,0	12,0	2,00	27,0	60
TR 14-1.5 WR	11,0	14,0	1,50	16,0	80
TR 14-2 WR	10,0	14,0	2,00	22,0	75
TR 15-1.5 WR	12,0	15,0	1,50	15,0	90
TR 16-2 WR	12,0	16,0	2,00	19,0	95
TR 18-2 WR	14,0	18,0	2,00	16,0	100
TR 20-2 WR	16,0	20,0	2,00	14,0	120
TR 22-2 WR	18,0	22,0	2,00	13,0	150
TR 25-2.5 WR	20,0	25,0	2,50	14,0	150
TR 28-2.5 WR	23,0	28,0	2,50	13,0	150
TR 30-2.5 WR	25,0	30,0	2,50	8,0	260

BD = radni pritisak

### Varijante proizvoda

<b>TR WB</b>	Cev od plastike od PA 12, mekana, plava
<b>TR WGE</b>	Cev od plastike od PA 12, mekana, žuta
<b>TR WS</b>	Cev od plastike od PA 12, mekana, crna
<b>TR WT</b>	Cev od plastike od PA 12, mekana, transparentno