

Osobine

Oblast primene	Opšta primena npr. u industriji, kod građevinskih mašina, agrarne tehnike itd.
Priključak 1	metrički spoljni cilindrični navoj
Oblik zaptivke 1	24° unutrašnji konus
Norma	odgovarajući ISO 7241-1 serija A
Materijal	čelik
Površinska zaštita	galvanska prevlaka



Napomena

Nominalna širina 10, konstrukcija 3 i u ED varijanti dostupna

Opis

Utične spojnice omogućavaju brzo spajanje.

Napomene u vezi porudžbine

Ostale podatke o temperaturi i pritisku možete dobiti po zahtevu.

Artikal

Naziv	DN*	Serija	Ø za cev spolja (mm)	Priključni navoj	Konstrukciona veličina	Radni pritisak (bar)	SF skr.*	Temperatura mineralnog ulja min. (°C)	Temperatura mineralnog ulja max. (°C)
SKS 04 HL 2	4	L	6	M 12x1,5	2	250,0	4	-30	100
SKS 06 HL 2	6	L	8	M 14x1,5	2	250,0	4	-30	100
SKS 06 HL 3	6	L	8	M 14x1,5	3	225,0	4	-30	100
SKS 08 HL 2	8	L	10	M 16x1,5	2	250,0	4	-30	100
SKS 08 HL 3	8	L	10	M 16x1,5	3	225,0	4	-30	100
SKS 10 HL 3	10	L	12	M 18x1,5	3	225,0	4	-30	100
SKS 10 HL 3 ED	10	L	12	M 18x1,5	3	225,0	4	-30	100
SKS 10 HL 4	10	L	12	M 18x1,5	4	225,0	4	-30	100
SKS 13 HL 3	12	L	15	M 22x1,5	3	225,0	4	-30	100
SKS 13 HL 4	12	L	15	M 22x1,5	4	225,0	4	-30	100
SKS 16 HL 3	16	L	18	M 26x1,5	3	225,0	4	-30	100
SKS 16 HL 4	16	L	18	M 26x1,5	4	225,0	4	-30	100
SKS 16 HL 5	16	L	18	M 26x1,5	5	225,0	4	-30	100
SKS 20 HL 4	19	L	22	M 30x2	4	225,0	4	-30	100
SKS 20 HL 5	19	L	22	M 30x2	5	225,0	4	-30	100
SKS 25 HL 5	25	L	28	M 36x2	5	225,0	4	-30	100
SKS 04 HS 2	4	S	8	M 16x1,5	2	250,0	4	-30	100
SKS 06 HS 1	6	S	10	M 18x1,5	1	300,0	4	-25	100
SKS 06 HS 2	6	S	10	M 18x1,5	2	250,0	4	-30	100
SKS 06 HS 3	6	S	10	M 18x1,5	3	225,0	4	-30	100
SKS 08 HS 2	8	S	12	M 20x1,5	2	250,0	4	-30	100
SKS 08 HS 3	8	S	12	M 20x1,5	3	225,0	4	-30	100
SKS 10 HS 3	10	S	14	M 22x1,5	3	225,0	4	-30	100
SKS 10 HS 4	10	S	14	M 22x1,5	4	225,0	4	-30	100
SKS 13 HS 3	12	S	16	M 24x1,5	3	225,0	4	-30	100
SKS 13 HS 4	12	S	16	M 24x1,5	4	225,0	4	-30	100
SKS 16 HS 3	16	S	20	M 30x2	3	225,0	4	-25	100
SKS 16 HS 4	16	S	20	M 30x2	4	225,0	4	-30	100
SKS 16 HS 5	16	S	20	M 30x2	5	225,0	4	-30	100
SKS 20 HS 5	19	S	25	M 36x2	5	225,0	4	-30	100
SKS 25 HS 5	25	S	30	M 42x2	5	225,0	4	-30	100

DN = nominalni prečnik, nominalna širina – SF gek. = sigurnosni faktor povezan

Pribor

SKS ZUBS Zaštitni utikač od prašine utične spojnice, SKS..



