

# TKS OV HB

Temperirani utikač bez ventila

**HANSA FLEX**

## Osobine

Priključak 1 BSP spoljni cilindrični navoj

Oblik zaptivke 1 60° unutrašnji konus

Materijal Mesing



## Napomene u vezi porudžbine

Ostale podatke o temperaturi i pritisku možete dobiti po zahtevu.

## Artikal

Naziv	DN*	Priključni navoj	Utična dimenzija (mm)	Radni pritisak (bar)	SF skr.*	Temperatura mineralnog ulja min. (°C)	Temperatura mineralnog ulja max. (°C)	SW (mm)
TKS 09 OV 02 HB	2	G 1/8" -28	9	15,0	3	-15	150	11
TKS 09 OV 06 HB	6	G 1/4" -19	9	15,0	3	-15	150	15
TKS 09 OV 10 HB	10	G 3/8" -19	9	15,0	3	-15	150	17
TKS 13 OV 06 HB	6	G 1/4" -19	13	15,0	3	-15	150	15
TKS 13 OV 10 HB	10	G 3/8" -19	13	15,0	3	-15	150	17
TKS 13 OV 13 HB	12	G 1/2" -14	13	15,0	3	-15	150	22
TKS 19 OV 13 HB	12	G 1/2" -14	19	15,0	3	-15	150	22
TKS 19 OV 20 HB	19	G 3/4" -14	19	15,0	3	-15	150	27

DN = nominalni prečnik, nominalna širina – SF gek. = sigurnosni faktor povezan – SW = veličina ključa