

# TKS OV ROR

Temperirani utikač spojnice bez ventila

**HANSA FLEX**

## Osobine

**Priključak 1** Nastavak cevi na skraćivanje

**Materijal** Mesing



## Napomene u vezi porudžbine

Ostale podatke o temperaturi i pritisku možete dobiti po zahtevu.

## Artikal

Naziv	Cev spolja Ø (mm)	Utična dimenzija (mm)	Dužina (mm)	Radni pritisak (bar)	SF skr.*	Temperatura mineralnog ulja min. (°C)	Temperatura mineralnog ulja max. (°C)	SW (mm)
TKS 09 OV ROR 08 L 68	8	9	68	15,0	3	-15	150	9
TKS 09 OV ROR 08 L 100	8	9	100	15,0	3	-15	150	9
TKS 09 OV ROR 10 L 120	10	9	120	15,0	3	-15	150	11
TKS 09 OV ROR 10 L 240	10	9	240	15,0	3	-15	150	11
TKS 09 OV ROR 10 L 360	10	9	360	15,0	3	-15	150	11
TKS 13 OV ROR 14 L 150	14	13	150	15,0	3	-15	150	15
TKS 13 OV ROR 14 L 300	14	13	300	15,0	3	-15	150	15

DN = nominalni prečnik, nominalna širina – SF gek. = sigurnosni faktor povezan – SW = veličina kluča