

ND AB 45

Utična spojnica, DKR W45°

HANSA FLEX

Osobine

| | |
|--------------------|-----------------------|
| Priključak 1 | BSP navoj navrtke |
| Oblik zaptivke 1 | 60° spoljašnji konus |
| Skraćenica | DKR |
| Norma | ISO 8434-6 BS 5200 |
| Materijal | čelik |
| Površinska zaštita | galvanska prevlaka |



Napomena

Neoštećene mazalice se mogu ponovo koristiti.

Artikal

| Naziv | DN | Veličina | col | G1 | L1 (mm) | L2 (mm) | S1 |
|-------------|----|----------|------|------------|------------|------------|----|
| ND 06 AB 45 | 6 | 4 | 1/4" | G 1/4" -19 | 51,0 | 16,0 | 17 |
| ND 10 AB 45 | 10 | 6 | 3/8" | G 3/8" -19 | 58,0 | 18,0 | 19 |
| ND 13 AB 45 | 12 | 8 | 1/2" | G 1/2" -14 | 68,0 | 19,0 | 27 |
| ND 16 AB 45 | 16 | 10 | 5/8" | G 5/8" -14 | 81,0 | 21,0 | 30 |

Pribor

ND ASR GE, RO, BL Granični prsten za utičnu spojnicu