

ND FL / ND FS

Utična spojnica, BEL / BES

HANSA FLEX

Osobine

Priključak 1	Cevni nastavak
Oblik zaptivke 1	Priključak za rezni prsten
Skraćenica	BEL / BES
Norma	ISO 8434-1
Materijal	čelik
Površinska zaštita	galvanska prevlaka



Napomena

Neoštećene mazalice se mogu ponovo koristiti.

Završna montaža reznim prstenom mora se obaviti u kaljenom nastavku za predmontažu (VOM...).

Ne koristiti kod novih konstrukcija; za ND...FL preporučujemo: ND...AOL.

Artikal

Naziv	DN	Veličina	col	Seriya	D2 (mm)	L1 (mm)
ND 06 FL 04	6	4	1/4"	L	6,0	44,0
ND 06 FL	6	4	1/4"	L	8,0	44,0
ND 10 FL 08	10	6	3/8"	L	10,0	49,0
ND 10 FL	10	6	3/8"	L	12,0	49,0
ND 13 FL 10	12	8	1/2"	L	12,0	54,0
ND 13 FL	12	8	1/2"	L	15,0	55,0
ND 16 FL	16	10	5/8"	L	18,0	67,0
ND 20 FL	19	12	3/4"	L	22,0	69,0
ND 06 FS	6	4	1/4"	S	10,0	-

Pribor

ND ASR GE, RO, BL Granični prsten za utičnu spojnicu

Dodatni elementi

VOM Nastavak za predmontažu