

PA 500 SF6 A

Utična armatura, SFS

HANSA FLEX

Osobine

| | |
|---------------------------|---|
| Oblast primene | Utična armatura za creva HD 500 |
| Priključak 1 | SAE priključak prirubnice 6000 PSI |
| Oblik zaptivke 1 | ravno zaptivanje sa SF O-prstenom |
| Skraćenica | SFS |
| Norma | SAE J518 ISO 6162-2 |
| Uvezivanje | sa osiguračem kidanja (interlock) |
| Obim isporuke | Pritisna nazuvica + pritisni priključak |
| Materijal | čelik |
| Površinska zaštita | galvanska prevlaka |



Artikal

| Naziv | DN | Veličina | col | Veličina spojnice | D (mm) | H (mm) | L1 (mm) |
|-----------------|----|----------|--------|-------------------|-----------|-----------|------------|
| PA 720 SF6 | 19 | 12 | 3/4" | 3/4" | 41,3 | 8,8 | 124,5 |
| PA 720 SF6 25 | 19 | 12 | 3/4" | 1" | 47,6 | 9,6 | 129,0 |
| PA 725 SF6 20 | 25 | 16 | 1" | 3/4" | 41,3 | 8,8 | 134,0 |
| PA 725 SF6 | 25 | 16 | 1" | 1" | 47,6 | 9,6 | 146,5 |
| PA 725 SF6 32 | 25 | 16 | 1" | 1.1/4" | 54,0 | 10,4 | 151,0 |
| PA 532 SF6 25 A | 31 | 20 | 1.1/4" | 1" | 47,6 | 9,6 | 149,0 |
| PA 532 SF6 A | 31 | 20 | 1.1/4" | 1.1/4" | 54,0 | 10,4 | 162,5 |
| PA 532 SF6 40 A | 31 | 20 | 1.1/4" | 1.1/2" | 63,5 | 12,7 | 167,0 |
| PA 540 SF6 32 A | 38 | 24 | 1.1/2" | 1.1/4" | 54,0 | 10,4 | 162,0 |
| PA 540 SF6 A | 38 | 24 | 1.1/2" | 1.1/2" | 63,5 | 12,7 | 183,5 |
| PA 540 SF6 50 A | 38 | 24 | 1.1/2" | 2" | 79,4 | 12,7 | 188,0 |
| PA 550 SF6 A | 51 | 32 | 2" | 2" | 79,4 | 12,7 | 202,0 |

Varijante proizvoda

PA 500 SF6 VA Utična armatura, SFS, plemeniti čelik