

# PA 500 SF6 A

Utična armatura, SFS

**HANSA FLEX**

## Osobine

**Oblast primene** Utična armatura za creva HD 500

**Priključak 1** SAE priključak prirubnice 6000 PSI

**Oblik zaptivke 1** ravno zaptivanje sa SF O-prstenom

**Skraćenica** SFS



**Norma** SAE J518  
ISO 6162-2

**Uvezivanje** sa osiguračem kidanja (interlock)

**Obim isporuke** Pritisna nazuvica + pritisni priključak

**Materijal** čelik

**Površinska zaštita** galvanska prevlaka



## Artikal

Naziv	DN	Veličina	col	Veličina spojnice	D (mm)	H (mm)	L1 (mm)
PA 720 SF6	19	12	3/4"	3/4"	41,3	8,8	124,5
PA 720 SF6 25	19	12	3/4"	1"	47,6	9,6	129,0
PA 725 SF6 20	25	16	1"	3/4"	41,3	8,8	134,0
PA 725 SF6	25	16	1"	1"	47,6	9,6	146,5
PA 725 SF6 32	25	16	1"	1.1/4"	54,0	10,4	151,0
PA 532 SF6 25 A	31	20	1.1/4"	1"	47,6	9,6	149,0
PA 532 SF6 A	31	20	1.1/4"	1.1/4"	54,0	10,4	162,5
PA 532 SF6 40 A	31	20	1.1/4"	1.1/2"	63,5	12,7	167,0
PA 540 SF6 32 A	38	24	1.1/2"	1.1/4"	54,0	10,4	162,0
PA 540 SF6 A	38	24	1.1/2"	1.1/2"	63,5	12,7	183,5
PA 540 SF6 50 A	38	24	1.1/2"	2"	79,4	12,7	188,0
PA 550 SF6 A	51	32	2"	2"	79,4	12,7	202,0

## Varijante proizvoda

PA 500 SF6 VA Utična armatura, SFS, plemeniti čelik