

PA 500 SF9 A

Utična armatura, SFS-CAT

Osobine

| | |
|---------------------------|---|
| Oblast primene | Utična armatura za creva HD 500 |
| Priključak 1 | SAE priključak priрубnice 6000 PSI |
| Oblik zaptivke 1 | ravno zaptivanje sa SF O-prstenom |
| Skraćenica | SFS-CAT |
| Podesno za | Caterpillar |
| Uvezivanje | sa osiguračem kidanja (interlock) |
| Obim isporuke | Pritisna nazuvica + pritisni priključak |
| Materijal | čelik |
| Površinska zaštita | galvanska prevlaka |



Artikal

| Naziv | DN | Veličina | col | Veličina spojnice | D (mm) | H (mm) | L1 (mm) |
|-----------------|----|----------|--------|-------------------|-----------|-----------|------------|
| PA 720 SF9 | 19 | 12 | 3/4" | 3/4" | 41,3 | 14,3 | 130,0 |
| PA 720 SF9 25 | 19 | 12 | 3/4" | 1" | 47,6 | 14,6 | 133,5 |
| PA 725 SF9 20 | 25 | 16 | 1" | 3/4" | 41,3 | 14,6 | 137,0 |
| PA 725 SF9 | 25 | 16 | 1" | 1" | 47,6 | 14,6 | 150,0 |
| PA 725 SF9 32 | 25 | 16 | 1" | 1.1/4" | 54,0 | 14,6 | 155,0 |
| PA 532 SF9 25 A | 31 | 20 | 1.1/4" | 1" | 47,6 | 14,6 | 150,0 |
| PA 532 SF9 A | 31 | 20 | 1.1/4" | 1.1/4" | 54,0 | 14,6 | 166,5 |
| PA 532 SF9 40 A | 31 | 20 | 1.1/4" | 1.1/4" | 63,5 | 14,6 | 168,5 |
| PA 540 SF9 32 A | 38 | 24 | 1.1/2" | 1.1/4" | 54,0 | 14,6 | 163,0 |
| PA 540 SF9 A | 38 | 24 | 1.1/2" | 1.1/2" | 63,5 | 14,6 | 185,0 |