


PA 700 SF 90

Utična armatura, SFL W90°

HANSA FLEX

Osobine

| | |
|---------------------------|---|
| Oblast primene | Utična armatura za creva HD 700 |
| Priključak 1 | SAE priključak priрубnice 3000 PSI |
| Oblik zaptivke 1 | ravno zaptivanje sa SF O-prstenom |
| Skraćenica | SFL |
| Norma | SAE J518 ISO 6162-1 |
| Uvezivanje | sa osiguračem kidanja (interlock) |
| Obim isporuke | Pritisna nazuvica + pritisni priključak |
| Materijal | čelik |
| Površinska zaštita | galvanska prevlaka |



Artikal

| Naziv | DN | Veličina | col | Veličina spojnice | Radni pritisak (bar) | D (mm) | H (mm) | L1 (mm) | L2 (mm) |
|----------------------|----|----------|--------|-------------------|----------------------|--------|--------|---------|---------|
| PA 713 SF 90 | 12 | 8 | 1/2" | 1/2" | 350,0 | 30,2 | 6,7 | 85,9 | 45,0 |
| PA 713 SF 20 90 | 12 | 8 | 1/2" | 3/4" | 350,0 | 38,1 | 6,7 | 96,0 | 51,0 |
| PA 720 SF 90 | 19 | 12 | 3/4" | 3/4" | 350,0 | 38,1 | 6,8 | 127,5 | 58,0 |
| PA 720 SF 90 L 95 | 19 | 12 | 3/4" | 3/4" | 350,0 | 38,1 | 6,8 | 127,5 | 95,0 |
| PA 720 SF 90 L 100 | 19 | 12 | 3/4" | 3/4" | 350,0 | 38,1 | 6,8 | 127,5 | 100,0 |
| PA 720 SF 90 L 120 | 19 | 12 | 3/4" | 3/4" | 350,0 | 38,1 | 6,8 | 127,5 | 120,0 |
| PA 720 SF 25 90 | 19 | 12 | 3/4" | 1" | - | 44,5 | 8,1 | 127,5 | 61,0 |
| PA 720 SF 25 90 L 82 | 19 | 12 | 3/4" | 1" | 320,0 | 44,5 | 8,1 | 127,5 | 82,0 |
| PA 725 SF 20 90 | 25 | 16 | 1" | 3/4" | 320,0 | 38,1 | 6,8 | 144,0 | 64,5 |
| PA 725 SF 90 | 25 | 16 | 1" | 1" | 320,0 | 44,5 | 8,1 | 158,0 | 67,0 |
| PA 725 SF 32 90 | 25 | 16 | 1" | 1.1/4" | 280,0 | 50,8 | 8,1 | 158,0 | 69,5 |
| PA 732 SF 25 90 S | 31 | 20 | 1.1/4" | 1" | 280,0 | 44,5 | 8,0 | 162,0 | 76,0 |
| PA 732 SF 90 S | 31 | 20 | 1.1/4" | 1.1/4" | 280,0 | 50,8 | 8,0 | 173,0 | 88,0 |
| PA 732 SF 40 90 S | 31 | 20 | 1.1/4" | 1.1/2" | 210,0 | 60,3 | 8,0 | 177,0 | 95,0 |
| PA 740 SF 32 90 | 38 | 24 | 1.1/2" | 1.1/4" | 210,0 | 50,8 | 8,1 | 190,5 | 93,0 |
| PA 740 SF 90 | 38 | 24 | 1.1/2" | 1.1/2" | 210,0 | 60,3 | 8,1 | 208,5 | 99,0 |
| PA 740 SF 50 90 | 38 | 24 | 1.1/2" | 2" | 210,0 | 71,4 | 9,6 | 218,0 | 104,0 |

Varijante proizvoda

PA 700 SF 90 VA Utična armatura, SFL W90°, plemeniti čelik