

PA 700 SF6 90

Utična armatura, SFS W90°

HANSA FLEX

Osobine

| | |
|---------------------------|---|
| Oblast primene | Utična armatura za creva HD 700 |
| Priključak 1 | SAE priključak prirubnice 6000 PSI |
| Oblik zaptivke 1 | ravno zaptivanje sa SF O-prstenom |
| Skraćenica | SFS |
| Norma | SAE J518 ISO 6162-2 |
| Uvezivanje | sa osiguračem kidanja (interlock) |
| Obim isporuke | Pritisna nazuvica + pritisni priključak |
| Materijal | čelik |
| Površinska zaštita | galvanska prevlaka |



Artikal

| Naziv | DN | Veličina | col | Veličina spojnice | Radni pritisak (bar) | D (mm) | H (mm) | L1 (mm) | L2 (mm) |
|------------------------|----|----------|--------|-------------------|----------------------|--------|--------|---------|---------|
| PA 713 SF6 90 | 12 | 8 | 1/2" | 1/2" | 420,0 | 31,8 | 7,7 | 86,0 | 46,0 |
| PA 713 SF6 20 90 | 12 | 8 | 1/2" | 3/4" | 420,0 | 41,3 | 8,8 | 92,5 | 46,0 |
| PA 716 SF6 13 90 | 16 | 10 | 5/8" | 1/2" | 420,0 | 31,8 | 7,7 | 108,0 | 48,0 |
| PA 716 SF6 20 90 | 16 | 10 | 5/8" | 3/4" | 420,0 | 41,3 | 8,8 | 107,5 | 52,5 |
| PA 716 SF6 25 90 | 16 | 10 | 5/8" | 1" | 420,0 | 47,6 | 9,5 | 108,0 | 57,0 |
| PA 720 SF6 13 90 L 80 | 19 | 12 | 3/4" | 1/2" | 420,0 | 31,8 | 7,8 | 117,0 | 80,0 |
| PA 720 SF6 13 90 L 100 | 19 | 12 | 3/4" | 1/2" | 420,0 | 31,8 | 7,8 | 117,0 | 100,0 |
| PA 720 SF6 90 | 19 | 12 | 3/4" | 3/4" | 420,0 | 41,3 | 8,8 | 127,5 | 62,0 |
| PA 720 SF6 90 L 52 | 19 | 12 | 3/4" | 3/4" | 420,0 | 41,3 | 8,8 | 127,5 | 52,0 |
| PA 720 SF6 90 L 80 | 19 | 12 | 3/4" | 3/4" | 420,0 | 41,3 | 8,8 | 127,5 | 80,0 |
| PA 720 SF6 90 L 85 | 19 | 12 | 3/4" | 3/4" | 420,0 | 41,3 | 8,8 | 127,5 | 85,0 |
| PA 720 SF6 90 L 100 | 19 | 12 | 3/4" | 3/4" | 420,0 | 41,3 | 8,8 | 127,5 | 100,0 |
| PA 720 SF6 90 L 150 | 19 | 12 | 3/4" | 3/4" | 420,0 | 41,3 | 8,8 | 127,5 | 150,0 |
| PA 720 SF6 25 90 | 19 | 12 | 3/4" | 1" | 420,0 | 47,6 | 9,6 | 127,5 | 68,0 |
| PA 725 SF6 20 90 | 25 | 16 | 1" | 3/4" | 420,0 | 41,3 | 8,8 | 152,5 | 70,5 |
| PA 725 SF6 90 | 25 | 16 | 1" | 1" | 420,0 | 47,6 | 9,6 | 158,0 | 74,0 |
| PA 725 SF6 90 L 100 | 25 | 16 | 1" | 1" | 420,0 | 47,6 | 9,6 | 158,0 | 100,0 |
| PA 725 SF6 90 L 200 | 25 | 16 | 1" | 1" | 420,0 | 47,6 | 9,6 | 158,0 | 200,0 |
| PA 725 SF6 32 90 | 25 | 16 | 1" | 1.1/4" | 420,0 | 54,0 | 10,4 | 156,0 | 83,5 |
| PA 732 SF6 25 90 S | 31 | 20 | 1.1/4" | 1" | 420,0 | 47,6 | 9,5 | 162,0 | 80,0 |
| PA 732 SF6 90 S | 31 | 20 | 1.1/4" | 1.1/4" | 420,0 | 54,0 | 10,3 | 173,5 | 94,5 |
| PA 732 SF6 90 L 120 S | 31 | 20 | 1.1/4" | 1.1/4" | 420,0 | 54,0 | 10,3 | 173,5 | 120,0 |
| PA 732 SF6 40 90 S | 31 | 20 | 1.1/4" | 1.1/2" | 420,0 | 63,5 | 12,6 | 174,5 | 100,0 |
| PA 740 SF6 32 90 | 38 | 24 | 1.1/2" | 1.1/4" | 420,0 | 54,0 | 10,3 | 193,0 | 100,0 |
| PA 740 SF6 90 | 38 | 24 | 1.1/2" | 1.1/2" | 420,0 | 63,5 | 12,6 | 213,5 | 110,0 |
| PA 740 SF6 50 90 | 38 | 24 | 1.1/2" | 2" | 420,0 | 79,4 | 12,6 | 215,5 | 126,0 |
| PA 750 SF6 90 | 51 | 32 | 2" | 2" | 420,0 | 79,4 | 12,6 | 268,0 | 138,0 |

Varijante proizvoda

PA 700 SF6 90 VA Utična armatura, SFS W90°, plemeniti čelik