

PN 02 AOL / PN 02 AOS

Pritisna nazuvica, DKOL / DKOS

HANSA FLEX

Osobine

| | |
|---------------------------|------------------------------------|
| Oblast primene | Merna tehnika |
| Priključak 1 | metrički navoj navrtke |
| Oblik zaptivke 1 | 24° spoljašnji konus sa O-prstenom |
| Skraćenica | DKOL |
| Norma | ISO 8434-1 |
| Materijal | čelik |
| Površinska zaštita | galvanska prevlaka |



Napomena

Odgovarajući priključak: PMH 102.

Artikal

| Naziv | DN | Veličina | col | Seriya | Ø za cev spolja (mm) | G1 | L1 (mm) | S1 | OR |
|--------------|----|----------|-------|--------|----------------------|------------|---------|----|-----------|
| PN 02 AOL 04 | 2 | 1 | 5/64" | L | 6 | M 12 x 1,5 | 35,0 | 14 | 4,0 x 1,5 |
| PN 02 AOL 06 | 2 | 1 | 5/64" | L | 8 | M 14 x 1,5 | 35,0 | 17 | 6,0 x 1,5 |
| PN 02 AOL 08 | 2 | 1 | 5/64" | L | 10 | M 16 x 1,5 | 36,5 | 19 | 7,5 x 1,5 |
| PN 02 AOL 10 | 2 | 1 | 5/64" | L | 12 | M 18 x 1,5 | 37,5 | 22 | 9,0 x 1,5 |
| PN 02 AOS 03 | 2 | 1 | 5/64" | S | 6 | M 14 x 1,5 | 35,0 | 17 | 4,0 x 1,5 |
| PN 02 AOS 04 | 2 | 1 | 5/64" | S | 8 | M 16 x 1,5 | 35,0 | 19 | 6,0 x 1,5 |
| PN 02 AOS 06 | 2 | 1 | 5/64" | S | 10 | M 18 x 1,5 | 36,5 | 22 | 7,5 x 1,5 |
| PN 02 AOS 08 | 2 | 1 | 5/64" | S | 12 | M 20 x 1,5 | 37,5 | 24 | 9,0 x 1,5 |

DN = nominalni prečnik, nominalna širina – Seriya: LL = veoma lako L = lako S = teško