

# PN A 45

Pritisna nazuvica, DKM W45°

**HANSA FLEX**

## Osobine

<b>Oblast primene</b>	Pritisna nazuvica za creva HD 100 do HD 400, KP, TE
<b>Priključak 1</b>	metrički navoj navrtke
<b>Oblik zaptivke 1</b>	60° zaptivna glava
<b>Skraćenica</b>	DKM
<b>Norma</b>	DIN 3863
<b>Materijal</b>	čelik
<b>Površinska zaštita</b>	galvanska prevlaka



## Napomena

Odgovarajući priključak molimo da odaberete prema tipu creva.

## Artikal

Naziv	DN	Veličina	col	Radni pritisak (bar)	G1	L1 (mm)	L2 (mm)	S1
PN 20 A 45	19	12	3/4"	63,0	M 30 x 1,5	119,0	29,0	36
PN 25 A 45	25	16	1"	63,0	M 38 x 1,5	148,0	39,0	46
PN 32 A 45	31	20	1.1/4"	63,0	M 45 x 1,5	-	-	-
PN 40 A 45	38	24	1.1/2"	63,0	M 52 x 1,5	172,0	44,0	60
PN 50 A 45	51	32	2"	40,0	M 65 x 2	209,0	53,0	75

## Varijante proizvoda

PN A 45 VA Pritisna nazuvica, DKM W45°, plemeniti čelik