

PN AFL 90

Pritisna nazuvica, DKL W90°

HANSA FLEX

Osobine

Oblast primene	Pritisna nazuvica za creva HD 100 do HD 400, KP, TE
Priključak 1	metrički navoj navrtke
Oblik zaptivke 1	24°/60° Universal sealing head
Skraćenica	DKL
Seriya	lak
Materijal	čelik
Površinska zaštita	galvanska prevlaka



Napomena

Odgovarajući priključak molimo da odaberete prema tipu creva.

Artikal

Naziv	DN	Veličina	col	Radni pritisak (bar)	G1	Ø za cev spolja (mm)	L1 (mm)	L2 (mm)	S1
PN 04 AFL 90	5	3	3/16"	250,0	M 12 x 1,5	6	48,5	29,0	14
PN 06 AFL 04 90	6	4	1/4"	250,0	M 12 x 1,5	6	57,0	30,5	14
PN 06 AFL 90	6	4	1/4"	250,0	M 14 x 1,5	8	55,0	30,0	17
PN 06 AFL 08 90	6	4	1/4"	250,0	M 16 x 1,5	10	55,0	31,0	19
PN 06 AFL 10 90	6	4	1/4"	250,0	M 18 x 1,5	12	62,5	35,0	22
PN 08 AFL 90	8	5	5/16"	250,0	M 16 x 1,5	10	58,0	30,0	19
PN 08 AFL 10 90	8	5	5/16"	250,0	M 18 x 1,5	12	58,0	30,5	22
PN 10 AFL 08 90	10	6	3/8"	250,0	M 16 x 1,5	10	63,0	38,0	19
PN 10 AFL 90	10	6	3/8"	250,0	M 18 x 1,5	12	64,0	35,0	22
PN 10 AFL 13 90	10	6	3/8"	250,0	M 22 x 1,5	15	64,0	35,5	27
PN 13 AFL 90	12	8	1/2"	250,0	M 22 x 1,5	15	72,5	39,5	27
PN 13 AFL 16 90	12	8	1/2"	160,0	M 26 x 1,5	18	83,5	49,5	32
PN 16 AFL 13 90	16	10	5/8"	160,0	M 22 x 1,5	15	87,0	49,5	27
PN 16 AFL 90	16	10	5/8"	160,0	M 26 x 1,5	18	88,0	49,5	32
PN 20 AFL 90	19	12	3/4"	160,0	M 30 x 2	22	99,5	54,5	36
PN 25 AFL 90	25	16	1"	100,0	M 36 x 2	28	127,0	66,0	41
PN 32 AFL 90	31	20	1.1/4"	100,0	M 45 x 2	35	151,5	82,0	50
PN 40 AFL 90	38	24	1.1/2"	100,0	M 52 x 2	42	176,5	95,0	60

Varijante proizvoda

PN AFL 90 VA Pritisna nazuvica, DKL W90°, plemeniti čelik