


PN B

Pritisna nazuvica, RGN

HANSA FLEX

Osobine

Oblast primene	Pritisna nazuvica za creva HD 100 do HD 400, KP, TE
Priključak 1	Ušica za metrički šuplji zavrtnj
Oblik zaptivke 1	zaptivanje bakarnim prstenom
Skraćenica	RGN
Norma	DIN 7642
Materijal	čelik
Površinska zaštita	galvanska prevlaka



Napomena

Odgovarajući priključak molimo da odaberete prema tipu creva.

Artikal

Naziv	DN	Veličina	col	Radni pritisak (bar)	D1 (mm)	za šuplji zavrtnj	L1 (mm)
PN 04 B	5	3	3/16"	200,0	10,1	M 10	42,0
PN 06 B 02	6	4	1/4"	200,0	8,1	M 8	48,0
PN 06 B 04	6	4	1/4"	200,0	10,1	M 10	48,0
PN 06 B	6	4	1/4"	200,0	12,1	M 12	46,5
PN 06 B 08	6	4	1/4"	200,0	14,1	M 14	49,5
PN 06 B 10	6	4	1/4"	200,0	16,1	M 16	52,5
PN 08 B 04	8	5	5/16"	200,0	10,1	M 10	48,0
PN 08 B 06	8	5	5/16"	200,0	12,1	M 12	54,5
PN 08 B	8	5	5/16"	200,0	14,1	M 14	54,5
PN 08 B 10	8	5	5/16"	200,0	16,1	M 16	52,5
PN 08 B 13	8	5	5/16"	200,0	18,1	M 18	55,5
PN 10 B 08	10	6	3/8"	200,0	14,1	M 14	56,0
PN 10 B	10	6	3/8"	200,0	16,1	M 16	54,0
PN 10 B 13	10	6	3/8"	200,0	18,1	M 18	57,0
PN 13 B	12	8	1/2"	200,0	18,1	M 18	58,0
PN 13 B 16	12	8	1/2"	200,0	22,1	M 22	60,5
PN 16 B 13	16	10	5/8"	200,0	18,1	M 18	68,5
PN 16 B	16	10	5/8"	200,0	22,1	M 22	69,5
PN 16 B 20	16	10	5/8"	200,0	26,1	M 26	72,0
PN 20 B 16	19	12	3/4"	200,0	22,1	M 22	76,0
PN 20 B	19	12	3/4"	200,0	26,1	M 26	78,5
PN 20 B 25	19	12	3/4"	200,0	30,1	M 30	82,0
PN 25 B	25	16	1"	200,0	30,1	M 30	90,0

Varijante proizvoda

PN B VA Pritisna nazuvica, RGN, plemeniti čelik