


# PN B

Pritisna nazuvica, RGN

**HANSA FLEX**

## Osobine

<b>Oblast primene</b>	Pritisna nazuvica za creva HD 100 do HD 400, KP, TE
<b>Priključak 1</b>	Ušica za metrički šuplji zavrtnj
<b>Oblik zaptivke 1</b>	zaptivanje bakarnim prstenom
<b>Skraćenica</b>	RGN
<b>Norma</b>	DIN 7642
<b>Materijal</b>	čelik
<b>Površinska zaštita</b>	galvanska prevlaka



## Napomena

Odgovarajući priključak molimo da odaberete prema tipu creva.

## Artikal

Naziv	DN	Veličina	col	Radni pritisak (bar)	D1 (mm)	za šuplji zavrtnj	L1 (mm)
PN 04 B	5	3	3/16"	200,0	10,1	M 10	42,0
PN 06 B 02	6	4	1/4"	200,0	8,1	M 8	48,0
PN 06 B 04	6	4	1/4"	200,0	10,1	M 10	48,0
PN 06 B	6	4	1/4"	200,0	12,1	M 12	46,5
PN 06 B 08	6	4	1/4"	200,0	14,1	M 14	49,5
PN 06 B 10	6	4	1/4"	200,0	16,1	M 16	52,5
PN 08 B 04	8	5	5/16"	200,0	10,1	M 10	48,0
PN 08 B 06	8	5	5/16"	200,0	12,1	M 12	54,5
PN 08 B	8	5	5/16"	200,0	14,1	M 14	54,5
PN 08 B 10	8	5	5/16"	200,0	16,1	M 16	52,5
PN 08 B 13	8	5	5/16"	200,0	18,1	M 18	55,5
PN 10 B 08	10	6	3/8"	200,0	14,1	M 14	56,0
PN 10 B	10	6	3/8"	200,0	16,1	M 16	54,0
PN 10 B 13	10	6	3/8"	200,0	18,1	M 18	57,0
PN 13 B	12	8	1/2"	200,0	18,1	M 18	58,0
PN 13 B 16	12	8	1/2"	200,0	22,1	M 22	60,5
PN 16 B 13	16	10	5/8"	200,0	18,1	M 18	68,5
PN 16 B	16	10	5/8"	200,0	22,1	M 22	69,5
PN 16 B 20	16	10	5/8"	200,0	26,1	M 26	72,0
PN 20 B 16	19	12	3/4"	200,0	22,1	M 22	76,0
PN 20 B	19	12	3/4"	200,0	26,1	M 26	78,5
PN 20 B 25	19	12	3/4"	200,0	30,1	M 30	82,0
PN 25 B	25	16	1"	200,0	30,1	M 30	90,0

## Varijante proizvoda

PN B VA Pritisna nazuvica, RGN, plemeniti čelik