


# PN FL 90

Pritisna nazuvica, BEL W90°

**HANSA FLEX**

## Osobine

<b>Oblast primene</b>	Pritisna nazuvica za creva HD 100 do HD 400, KP, TE
<b>Priključak 1</b>	Cevni nastavak
<b>Oblik zaptivke 1</b>	Priključak za rezni prsten
<b>Skraćenica</b>	BEL
<b>Norma</b>	ISO 8434-1
<b>Seriya</b>	lak
<b>Materijal</b>	čelik
<b>Površinska zaštita</b>	galvanska prevlaka



## Napomena

Završna montaža reznim prstenom mora se obaviti u kaljenom nastavku za predmontažu (VOM...).

Odgovarajući priključak molimo da odaberete prema tipu creva.

Ne koristiti kod novih konstrukcija; preporučujemo: PN...AOL...90.

## Artikal

Naziv	DN	Veličina	col	Radni pritisak (bar)	D2 (mm)	L1 (mm)	L2 (mm)
PN 04 FL 90	5	3	3/16"	250,0	6,0	47,5	41,5
PN 06 FL 04 90	6	4	1/4"	250,0	6,0	56,5	42,5
PN 06 FL 90	6	4	1/4"	250,0	8,0	56,5	43,5
PN 08 FL 06 90	8	5	5/16"	250,0	8,0	56,5	43,5
PN 08 FL 90	8	5	5/16"	250,0	10,0	58,5	44,0
PN 10 FL 08 90	10	6	3/8"	250,0	10,0	61,5	53,5
PN 10 FL 90	10	6	3/8"	250,0	12,0	62,0	52,5
PN 10 FL 13 90	10	6	3/8"	250,0	15,0	77,5	48,0
PN 13 FL 10 90	12	8	1/2"	250,0	12,0	62,0	52,5
PN 13 FL 90	12	8	1/2"	250,0	15,0	72,5	55,0
PN 13 FL 16 90	12	8	1/2"	160,0	18,0	72,5	58,5
PN 16 FL 90	16	10	5/8"	160,0	18,0	83,0	70,0
PN 16 FL 20 90	16	10	5/8"	160,0	22,0	83,0	74,0
PN 20 FL 16 90	19	12	3/4"	160,0	18,0	88,0	70,0
PN 20 FL 90	19	12	3/4"	160,0	22,0	100,0	73,5
PN 25 FL 90	25	16	1"	100,0	28,0	127,5	84,5
PN 32 FL 90	31	20	1.1/4"	100,0	35,0	149,5	106,0
PN 40 FL 90	38	24	1.1/2"	100,0	42,0	167,0	99,0

## Varijante proizvoda

PN FL 90 VA Pritisna nazuvica, BEL W90°, plemeniti čelik

## Dodatni elementi

VOM Nastavak za predmontažu