


PN FS 90

Pritisna nazuvica, BES W90°

HANSA FLEX

Osobine

Oblast primene	Pritisna nazuvica za creva HD 100 do HD 400, KP, TE
Priključak 1	Cevni nastavak
Oblik zaptivke 1	Priključak za rezni prsten
Skraćenica	BES
Norma	ISO 8434-1
Seriya	težak
Materijal	čelik
Površinska zaštita	galvanska prevlaka



Napomena

Završna montaža reznim prstenom mora se obaviti u kaljenom nastavku za predmontažu (VOM...).

Odgovarajući priključak molimo da odaberete prema tipu creva.

Ne koristiti kod novih konstrukcija; preporučujemo: PN...AOS...90.

Artikal

Naziv	DN	Veličina	col	Radni pritisak (bar)	D2 (mm)	L1 (mm)	L2 (mm)
PN 04 FS 90	5	3	3/16"	630,0	8,0	59,0	37,0
PN 06 FS 04 90	6	4	1/4"	630,0	8,0	56,5	43,5
PN 06 FS 90	6	4	1/4"	630,0	10,0	56,5	44,5
PN 06 FS 08 90	6	4	1/4"	630,0	12,0	56,5	44,5
PN 08 FS 90	8	5	5/16"	630,0	12,0	57,0	46,5
PN 10 FS 90	10	6	3/8"	630,0	14,0	58,5	60,5
PN 13 FS 08 90	12	8	1/2"	400,0	12,0	58,5	46,5
PN 13 FS 10 90	12	8	1/2"	400,0	14,0	70,5	61,5
PN 13 FS 90	12	8	1/2"	400,0	16,0	71,5	63,5
PN 16 FS 13 90	16	10	5/8"	400,0	16,0	76,0	63,5
PN 16 FS 90	16	10	5/8"	400,0	20,0	83,0	80,5
PN 20 FS 16 90	19	12	3/4"	400,0	20,0	100,0	80,0
PN 20 FS 90	19	12	3/4"	400,0	25,0	100,0	85,5
PN 25 FS 20 90	25	16	1"	250,0	25,0	127,5	94,5
PN 25 FS 90	25	16	1"	250,0	30,0	127,5	99,5
PN 32 FS 25 90	31	20	1.1/4"	250,0	30,0	135,0	99,5
PN 32 FS 90	31	20	1.1/4"	250,0	38,0	156,0	105,0
PN 40 FS 32 90	38	24	1.1/2"	250,0	38,0	159,5	105,0

Varijante proizvoda

PN FS 90 VA Pritisna nazuvica, BES W90°, plemeniti čelik