


PN HJOF

Pritisna nazuvica, ORFS

HANSA FLEX

Osobine

| | |
|---------------------------|---|
| Oblast primene | Pritisna nazuvica za creva HD 100 do HD 400, KP, TE |
| Priključak 1 | UN/UNF spoljni navoj |
| Oblik zaptivke 1 | ravno zaptivanje sa O-prstenom |
| Skraćenica | ORFS |
| Norma | ISO 8434-3 |
| Materijal | čelik |
| Površinska zaštita | galvanska prevlaka |



Napomena

Odgovarajući priključak molimo da odaberete prema tipu creva.

Artikal

| Naziv | DN | Veličina | col | G1 | L1 (mm) | S1 | OR |
|---------------|----|----------|--------|-----------------|------------|----|--------------|
| PN 06 HJOF | 6 | 4 | 1/4" | 9/16" -18 UNF | 52,5 | 17 | 7,65 x 1,78 |
| PN 06 HJOF 10 | 6 | 4 | 1/4" | 11/16" -16 UN | 54,0 | 19 | 9,25 x 1,78 |
| PN 08 HJOF 10 | 8 | 5 | 5/16" | 11/16" -16 UN | 54,0 | 19 | 9,25 x 1,78 |
| PN 10 HJOF | 10 | 6 | 3/8" | 11/16" -16 UN | 56,0 | 19 | 9,25 x 1,78 |
| PN 10 HJOF 13 | 10 | 6 | 3/8" | 13/16" -16 UN | 58,5 | 22 | 12,42 x 1,78 |
| PN 10 HJOF 16 | 10 | 6 | 3/8" | 1" -14 UNS | 62,0 | 27 | 15,60 x 1,78 |
| PN 13 HJOF | 12 | 8 | 1/2" | 13/16" -16 UN | 60,0 | 22 | 12,42 x 1,78 |
| PN 13 HJOF 16 | 12 | 8 | 1/2" | 1" -14 UNS | 63,5 | 27 | 15,60 x 1,78 |
| PN 13 HJOF 20 | 12 | 8 | 1/2" | 1.3/16" -12 UN | 66,5 | 32 | 18,77 x 1,78 |
| PN 16 HJOF | 16 | 10 | 5/8" | 1" -14 UNS | 68,0 | 27 | 15,60 x 1,78 |
| PN 16 HJOF 20 | 16 | 10 | 5/8" | 1.3/16" -12 UN | 71,0 | 32 | 18,77 x 1,78 |
| PN 20 HJOF | 19 | 12 | 3/4" | 1.3/16" -12 UN | 78,0 | 32 | 18,77 x 1,78 |
| PN 20 HJOF 25 | 19 | 12 | 3/4" | 1.7/16" -12 UN | 82,5 | 41 | 23,52 x 1,78 |
| PN 25 HJOF | 25 | 16 | 1" | 1.7/16" -12 UN | 90,5 | 41 | 23,52 x 1,78 |
| PN 32 HJOF | 31 | 20 | 1.1/4" | 1.11/16" -12 UN | 101,5 | 46 | 29,87 x 1,78 |
| PN 40 HJOF | 38 | 24 | 1.1/2" | 2" -12 UN | 109,0 | 55 | 37,82 x 1,78 |