

PN SF9 90

Pritisna nazuvica, SFS-CAT W90°

HANSA FLEX

Osobine

Oblast primene	Pritisna nazuvica za creva HD 100 do HD 400, KP, TE
Priključak 1	SAE priključak prirubnice 6000 PSI
Oblik zaptivke 1	ravno zaptivanje sa SF O-prstenom
Skraćenica	SFS-CAT
Podesno za	Caterpillar
Materijal	čelik
Površinska zaštita	galvanska prevlaka



Napomena

Odgovarajući priključak molimo da odaberete prema tipu creva.

Artikal

Naziv	DN	Veličina	col	Veličina spojnice	Radni pritisak (bar)	D (mm)	H (mm)	L1 (mm)	L2 (mm)
PN 20 SF9 90	19	12	3/4"	3/4"	420,0	41,3	14,6	99,0	66,5
PN 20 SF9 25 90	19	12	3/4"	1"	420,0	47,6	14,6	99,0	71,5
PN 25 SF9 90	25	16	1"	1"	420,0	47,6	14,6	126,0	79,0
PN 25 SF9 32 90	25	16	1"	1.1/4"	420,0	54,0	14,6	126,0	85,5
PN 32 SF9 90	31	20	1.1/4"	1.1/4"	420,0	54,0	14,6	150,5	94,5
PN 32 SF9 40 90	31	20	1.1/4"	1.1/2"	420,0	63,5	14,6	150,5	100,5
PN 40 SF9 90	38	24	1.1/2"	1.1/2"	420,0	63,5	14,6	175,5	110,0