

# SIN HB

Pritisna nazuvica, AGR

**HANSA FLEX**

## Osobine

Priključak 1 BSP spoljni cilindrični navoj

Oblik zaptivke 1 60° unutrašnji konus

Skraćenica AGR

Norma ISO 228-1  
ISO 8434-6  
BS 5200

Materijal Mesing



## Napomena

Odgovarajući priključak molimo da odaberete prema tipu creva.

## Artikal

| Naziv        | DN | Veličina | col   | Ø D<br>(mm) | G1         |
|--------------|----|----------|-------|-------------|------------|
| SIN 03 HB 04 | 3  | 2        | 1/8"  | 5,0         | G 1/8" -28 |
| SIN 04 HB 06 | 4  | 3        | 3/16" | 6,0         | G 1/4" -19 |
| SIN 06 HB    | 6  | 4        | 1/4"  | 8,0         | G 1/4" -19 |
| SIN 06 HB 10 | 6  | 4        | 1/4"  | 8,0         | G 3/8" -19 |
| SIN 08 HB 10 | 8  | 5        | 5/16" | 10,0        | G 3/8" -19 |
| SIN 10 HB 13 | 10 | 6        | 3/8"  | 12,0        | G 1/2" -14 |
| SIN 13 HB    | 12 | 8        | 1/2"  | 15,0        | G 1/2" -14 |