

GMM 160

Manometar sa glicerinskim punjenjem

HANSA FLEX

Osobine

| | |
|--------------------|---|
| Konstrukcija | Pipe spring pressure gauge with glycerine filling |
| Priključak 1 | BSP spoljni cilindrični navoj |
| Oblik zaptivke 1 | ravno zaptivanje sa rukavcem |
| Priključak | dole |
| Norma | EN 837-1 |
| Prigušivanje | pomoću glicerinskog punjenja |
| Temperaturni opseg | medija maks. +60 °C Okoline -20 °C do +60 °C |



Napomena

Područje primene kod mirnog opterećenja: 3/4 x vrednost na skali.

Područje primene kod promenljivog opterećenja: 2/3 x vrednost na skali.

Artikal

| Naziv | Nominalna veličina Ø | Opseg skale | Klasa kvaliteta | Priključak |
|--------------|----------------------|-------------|-----------------|------------|
| GMM 160-0.6 | 160 | 0...0,6 | 1,0 | G 1/2" -14 |
| GMM 160-1 | 160 | 0...1 | 1,0 | G 1/2" -14 |
| GMM 160-1.6 | 160 | 0...1,6 | 1,0 | G 1/2" -14 |
| GMM 160-2.5 | 160 | 0...2,5 | 1,0 | G 1/2" -14 |
| GMM 160-4 | 160 | 0...4 | 1,0 | G 1/2" -14 |
| GMM 160-6 | 160 | 0...6 | 1,0 | G 1/2" -14 |
| GMM 160-10 | 160 | 0...10 | 1,0 | G 1/2" -14 |
| GMM 160-16 | 160 | 0...16 | 1,0 | G 1/2" -14 |
| GMM 160-25 | 160 | 0...25 | 1,0 | G 1/2" -14 |
| GMM 160-40 | 160 | 0...40 | 1,0 | G 1/2" -14 |
| GMM 160-60 | 160 | 0...60 | 1,0 | G 1/2" -14 |
| GMM 160-100 | 160 | 0...100 | 1,0 | G 1/2" -14 |
| GMM 160-160 | 160 | 0...160 | 1,0 | G 1/2" -14 |
| GMM 160-250 | 160 | 0...250 | 1,0 | G 1/2" -14 |
| GMM 160-400 | 160 | 0...400 | 1,0 | G 1/2" -14 |
| GMM 160-600 | 160 | 0...600 | 1,0 | G 1/2" -14 |
| GMM 160-1000 | 160 | 0...1000 | 1,0 | G 1/2" -14 |