

GMM 160

Manometar sa glicerinskim punjenjem

HANSA FLEX

Osobine

Konstrukcija	Pipe spring pressure gauge with glycerine filling
Priključak 1	BSP spoljni cilindrični navoj
Oblik zaptivke 1	ravno zaptivanje sa rukavcem
Priključak	dole
Norma	EN 837-1
Prigušivanje	pomoću glicerinskog punjenja
Temperaturni opseg	medija maks. +60 °C Okoline -20 °C do +60 °C



Napomena

Područje primene kod mirnog opterećenja: 3/4 x vrednost na skali.

Područje primene kod promenljivog opterećenja: 2/3 x vrednost na skali.

Artikal

Naziv	Nominalna veličina Ø	Opseg skale	Klasa kvaliteta	Priključak
GMM 160-0.6	160	0...0,6	1,0	G 1/2" -14
GMM 160-1	160	0...1	1,0	G 1/2" -14
GMM 160-1.6	160	0...1,6	1,0	G 1/2" -14
GMM 160-2.5	160	0...2,5	1,0	G 1/2" -14
GMM 160-4	160	0...4	1,0	G 1/2" -14
GMM 160-6	160	0...6	1,0	G 1/2" -14
GMM 160-10	160	0...10	1,0	G 1/2" -14
GMM 160-16	160	0...16	1,0	G 1/2" -14
GMM 160-25	160	0...25	1,0	G 1/2" -14
GMM 160-40	160	0...40	1,0	G 1/2" -14
GMM 160-60	160	0...60	1,0	G 1/2" -14
GMM 160-100	160	0...100	1,0	G 1/2" -14
GMM 160-160	160	0...160	1,0	G 1/2" -14
GMM 160-250	160	0...250	1,0	G 1/2" -14
GMM 160-400	160	0...400	1,0	G 1/2" -14
GMM 160-600	160	0...600	1,0	G 1/2" -14
GMM 160-1000	160	0...1000	1,0	G 1/2" -14