

RMM 63 H

Manometar bez glicerinskog punjenja

HANSA FLEX

Osobine

Konstrukcija	Pipe spring pressure gauge without glycerine filling
Priključak 1	BSP spoljni cilindrični navoj
Oblik zaptivke 1	ravno zaptivanje sa rukavcem
Priključak	pozadi, centrično
Norma	EN 837-1
Temperaturni opseg	medija maks. +60 °C Okoline -20 °C do +60 °C



Napomena

Područje primene kod mirnog opterećenja: 3/4 x vrednost na skali.

Područje primene kod promenljivog opterećenja: 2/3 x vrednost na skali.

Artikal

Naziv	Nominalna veličina Ø	Opseg skale	Klasa kvaliteta	Priključak
RMM 63-0.6 H	63	0...0,6	2,5	G 1/4" -19
RMM 63-1 H	63	0...1	2,5	G 1/4" -19
RMM 63-1.6 H	63	0...1,6	2,5	G 1/4" -19
RMM 63-2.5 H	63	0...2,5	2,5	G 1/4" -19
RMM 63-4 H	63	0...4	2,5	G 1/4" -19
RMM 63-6 H	63	0...6	2,5	G 1/4" -19
RMM 63-10 H	63	0...10	2,5	G 1/4" -19
RMM 63-16 H	63	0...16	2,5	G 1/4" -19
RMM 63-25 H	63	0...25	2,5	G 1/4" -19
RMM 63-40 H	63	0...40	2,5	G 1/4" -19
RMM 63-60 H	63	0...60	2,5	G 1/4" -19
RMM 63-100 H	63	0...100	2,5	G 1/4" -19
RMM 63-160 H	63	0...160	2,5	G 1/4" -19
RMM 63-250 H	63	0...250	2,5	G 1/4" -19
RMM 63-315 H	63	0...315	2,5	G 1/4" -19
RMM 63-400 H	63	0...400	2,5	G 1/4" -19