

# 2 OK

Kopča sa 2 usiče


**HANSA FLEX**

## Osobine

**Oblast primene** Držači creva za opseg niskog pritiska

**Materijal** čelik

**Površinska zaštita** galvanska prevlaka



## Artikal

Naziv	Opseg rastezanja (mm)	Širina trake (mm)
2 OK 5-7	5 - 7	6,0
2 OK 7-9	7 - 9	6,0
2 OK 9-11	9 - 11	6,5
2 OK 11-13	11 - 13	6,5
2 OK 13-15	13 - 15	7,0
2 OK 14-17	14 - 17	7,0
2 OK 15-18	15 - 18	7,5
2 OK 17-20	17 - 20	7,5
2 OK 18-21	18 - 21	8,0
2 OK 20-23	20 - 23	8,0
2 OK 22-25	22 - 25	8,5
2 OK 23-27	23 - 27	8,5
2 OK 25-28	25 - 28	9,0
2 OK 28-31	28 - 31	9,0
2 OK 31-34	31 - 34	9,5
2 OK 34-37	34 - 37	9,5
2 OK 37-40	37 - 40	10,0
2 OK 40-43	40 - 43	10,0
2 OK 43-46	43 - 46	10,0

## Varijante proizvoda

2 OK VC Kopča sa 2 usiče, pocinkovan, hrom sjaj

2 OK VA Kopča sa 2 usiče, plemeniti čelik