

# 2 OK VA

Kopča sa 2 usiče

## Osobine

**Oblast primene** Držači creva za opseg niskog pritiska

**Materijal** plemeniti čelik



## Artikal

| Naziv           | Opseg rastezanja (mm) | Širina trake (mm) |
|-----------------|-----------------------|-------------------|
| 2 OK 3-5 VA     | 3,4 - 5,0             | 5,0               |
| 2 OK 3.1-4.1 VA | 3,1 - 4,1             | 3,5               |
| 2 OK 3.5-4.5 VA | 3,5 - 4,5             | 3,5               |
| 2 OK 5-7 VA     | 5,0 - 7,0             | 6,0               |
| 2 OK 7-9 VA     | 7,0 - 9,0             | 6,0               |
| 2 OK 8-11 VA    | 8,0 - 11,0            | 7,0               |
| 2 OK 9-11 VA    | 9,0 - 11,0            | 6,5               |
| 2 OK 11-13 VA   | 11,0 - 13,0           | 6,5               |
| 2 OK 13-15 VA   | 13,0 - 15,0           | 7,0               |
| 2 OK 15-17 VA   | 15,0 - 17,0           | 7,5               |
| 2 OK 15-18 VA   | 15,0 - 18,0           | 7,5               |
| 2 OK 17-20 VA   | 17,0 - 20,0           | 7,5               |
| 2 OK 18-21 VA   | 18,0 - 21,0           | 8,0               |
| 2 OK 19-22 VA   | 18,1 - 22,0           | 9,0               |
| 2 OK 20-23 VA   | 20,0 - 23,0           | 8,0               |
| 2 OK 22-25 VA   | 22,0 - 25,0           | 8,5               |
| 2 OK 23-27 VA   | 23,0 - 27,0           | 8,5               |
| 2 OK 25-28 VA   | 25,0 - 28,0           | 9,0               |
| 2 OK 27-31 VA   | 26,3 - 31,0           | 10,0              |
| 2 OK 28-31 VA   | 28,0 - 31,0           | 9,0               |
| 2 OK 31-34 VA   | 31,0 - 34,0           | 9,5               |
| 2 OK 34-37 VA   | 34,0 - 37,0           | 9,5               |
| 2 OK 37-40 VA   | 37,0 - 40,0           | 10,0              |
| 2 OK 40-43 VA   | 40,0 - 43,0           | 10,0              |
| 2 OK 43-46 VA   | 43,0 - 46,0           | 10,0              |

## Varijante proizvoda

2 OK Kopča sa 2 usiče, galvanska prevlaka

2 OK VC Kopča sa 2 usiče, pocinkovan, hrom sjaj