

SRS 1-6 PA G

Cevna obujmica, laka konstrukcija

HANSA FLEX


Osobine

Dodatak za vrstu konstrukciju Glatka unutrašnja strana obujmice

Seriya lak

Norma DIN 3015-1

Materijal poliamid 6



Napomena

Za držač creva i kabla preporučuje se upotreba obujmice sa glatkom unutrašnjom površinom. Montaža se odvija bez prednaprezanja, pri čemu se visina bloka H smanjuje za zazor S1.

Napomene u vezi porudžbine

1 komad = 2 polovice obujmice

Artikal

| Naziv | Cev spolja Ø d2 (mm) | Cev spolja Ø d2 | Veličina obujmice | e1 (mm) | H (mm) | L (mm) | S1 (mm) |
|------------------|----------------------|-----------------|-------------------|---------|--------|--------|---------|
| SRS 106 A PA G | 6,0 | - | 1 | 20 | 27 | 34 | 0,6 |
| SRS 106.4 A PA G | 6,4 | 1/4" | 1 | 20 | 27 | 34 | 0,6 |
| SRS 108 A PA G | 8,0 | 5/16" | 1 | 20 | 27 | 34 | 0,6 |
| SRS 109.5 A PA G | 9,5 | 3/8" | 1 | 20 | 27 | 34 | 0,6 |
| SRS 110 A PA G | 10,0 | - | 1 | 20 | 27 | 34 | 0,6 |
| SRS 112 A PA G | 12,0 | - | 1 | 20 | 27 | 34 | 0,6 |
| SRS 0212.7 PA G | 12,7 | 1/2" | 2 | 26 | 33 | 40 | 0,8 |
| SRS 0213.5 PA G | 13,5 | - | 2 | 26 | 33 | 40 | 0,8 |
| SRS 0214 PA G | 14,0 | - | 2 | 26 | 33 | 40 | 0,8 |
| SRS 0215 PA G | 15,0 | - | 2 | 26 | 33 | 40 | 0,8 |
| SRS 0216 PA G | 16,0 | 5/8" | 2 | 26 | 33 | 40 | 0,8 |
| SRS 0217.2 PA G | 17,2 | - | 2 | 26 | 33 | 40 | 0,8 |
| SRS 0218 PA G | 18,0 | - | 2 | 26 | 33 | 40 | 0,8 |
| SRS 0319 PA G | 19,0 | 3/4" | 3 | 33 | 35 | 48 | 1,0 |
| SRS 0320 PA G | 20,0 | - | 3 | 33 | 35 | 48 | 1,0 |
| SRS 0321.3 PA G | 21,3 | - | 3 | 33 | 35 | 48 | 1,0 |
| SRS 0322 PA G | 22,0 | - | 3 | 33 | 35 | 48 | 1,0 |
| SRS 0325 PA G | 25,0 | 1" | 3 | 33 | 35 | 48 | 1,0 |
| SRS 0426.9 PA G | 26,9 | - | 4 | 40 | 42 | 57 | 1,2 |
| SRS 0428 PA G | 28,0 | - | 4 | 40 | 42 | 57 | 1,2 |
| SRS 0430 PA G | 30,0 | - | 4 | 40 | 42 | 57 | 1,2 |
| SRS 0532 PA G | 32,0 | 1.1/4" | 5 | 52 | 58 | 70 | 1,2 |
| SRS 0533.7 PA G | 33,7 | - | 5 | 52 | 58 | 70 | 1,2 |
| SRS 0535 PA G | 35,0 | - | 5 | 52 | 58 | 70 | 1,2 |
| SRS 0538 PA G | 38,0 | 1.1/2" | 5 | 52 | 58 | 70 | 1,2 |
| SRS 0540 PA G | 40,0 | - | 5 | 52 | 58 | 70 | 1,2 |
| SRS 0542 PA G | 42,0 | - | 5 | 52 | 58 | 70 | 1,2 |
| SRS 0644.5 PA G | 44,5 | 1.3/4" | 6 | 66 | 66 | 86 | 1,2 |
| SRS 0645 PA G | 45,0 | - | 6 | 66 | 66 | 86 | 1,2 |
| SRS 0648 PA G | 48,0 | - | 6 | 66 | 66 | 86 | 1,2 |
| SRS 0650 PA G | 50,0 | - | 6 | 66 | 66 | 86 | 1,2 |
| SRS 0650.8 PA G | 50,8 | 2" | 6 | 66 | 66 | 86 | 1,2 |
| SRS 0652 PA G | 52,0 | - | 6 | 66 | 66 | 86 | 1,2 |
| SRS 0655 PA G | 55,0 | - | 6 | 66 | 66 | 86 | 1,2 |
| SRS 0657 PA G | 57,0 | 2.1/4" | 6 | 66 | 66 | 86 | 1,2 |

Varijante proizvoda

SRS 1-6 AL Cevna obujmica, laka konstrukcija, Unutrašnja strana obujmice sa rebrima

SRS 1-6 PA Cevna obujmica, laka konstrukcija, Unutrašnja strana obujmice sa rebrima

SRS 1-6 PP Cevna obujmica, laka konstrukcija, Unutrašnja strana obujmice sa rebrima

SRS 1-6 PP G Cevna obujmica, laka konstrukcija, Glatka unutrašnja strana obujmice

SRS 1-6 PA G

Cevna obujmica, laka konstrukcija

HANSA FLEX
