

# PN ARG

Pritisna nazuvica, priključak za gas

**HANSA FLEX**

## Osobine

Oblast primene	Pritisna nazuvica za creva HD 100 do HD 400, KP, TE
Podesno za	Nitrogen
Priključak 1	Gas connection nut thread
Oblik zaptivke 1	ravno zaptivanje
Materijal	
Površinska zaštita	galvanska prevlaka
Posebne karakteristike	Right-hand thread



## Napomena

Odgovarajući priključak molimo da odaberete prema tipu creva.

## Artikal

Naziv	DN	Veličina	col	za medijum	G1	L1 (mm)
PN 06 ARG 20	6	4	1/4"	Kiseonik	G 3/4"	-
PN 06 ARG 21	6	4	1/4"	argon / CO2	W 21,80 x 1/14"	62,5
PN 06 ARG 24	6	4	1/4"	nitrogen	W 24,32 x 1/14"	-
PN 10 ARG 20	10	6	3/8"	Kiseonik	G 3/4"	-
PN 10 ARG 21	10	6	3/8"	argon / CO2	W 21,80 x 1/14"	66,5
PN 10 ARG 24	10	6	3/8"	nitrogen	W 24,32 x 1/14"	-
PN 13 ARG 20	12	8	1/2"	Kiseonik	G 3/4"	-
PN 13 ARG 21	12	8	1/2"	argon / CO2	W 21,80 x 1/14"	66,0
PN 13 ARG 24	12	8	1/2"	nitrogen	W 24,32 x 1/14"	-