


# WA HN

Priključni deo ... HN temper liv

**HANSA FLEX**

## Osobine

<b>Oblast primene</b>	Priključna armatura za metalna creva
<b>Priključak 1</b>	colovani spoljašnji konusni navoj
<b>Oblik zaptivke 1</b>	zaptivanje preko navoja
<b>Norma</b>	DIN EN 10226 / ISO 7-1
<b>Konstrukcija</b>	pravo
<b>Materijal</b>	Temper liv
<b>Primena</b>	model sa lemom postojan na temperaturi do 200 °C



## Napomena

Navedene širine ključeva predstavljaju orijentacione vrednosti!

The specified working pressure PN(bar) relates to the working temperature of -20 °C to 120 °C. At working temperature of 120 °C to 200 °C the working pressure PN (bar) reduces to 22,7 bar.

## Napomene u vezi porudžbine

Ostali modeli na zahtev

## Artikal

Naziv	DN	PN (bar)	G1	SW (mm)
WA 006 HN	6	25	R 1/4"	19
WA 010 HN	10	25	R 3/8"	22
WA 013 HN	13	25	R 1/2"	28
WA 020 HN	20	25	R 3/4"	32
WA 025 HN	25	25	R 1"	42
WA 032 HN	32	25	R 1.1/4"	50
WA 040 HN	40	25	R 1.1/2"	55
WA 050 HN	50	25	R 2"	70
WA 065 HN	65	25	R 2.1/2"	85
WA 080 HN	80	25	R 3"	100
WA 100 HN	100	25	R 4"	130

## Varijante proizvoda

WA HN VA Priključni deo ... HN VA, plemeniti čelik