

WA VB

Priključni deo ... VB temper liv

HANSA FLEX

Osobine

| | |
|-------------------------|--|
| Oblast primene | Priključna armatura za metalna creva |
| Priključak 1 | colovani cilindrični unutrašnji navoj |
| Oblik zaptivke 1 | konusno zaptivanje |
| Norma | DIN EN 10226 / ISO 7-1 |
| Konstrukcija | pravo |
| Primena | model sa lemom postojan na temperaturi do 200 °C |
| Verzija | 3-delni navojni spoj |
| Materijal | Temper liv |



Napomena

Navedene širine ključeva predstavljaju orijentacione vrednosti!

The specified working pressure PN(bar) relates to the working temperature of -20 °C to 120 °C. At working temperature of 120 °C to 200 °C the working pressure PN (bar) reduces to 22,7 bar.

Napomene u vezi porudžbine

Ostali modeli na zahtev

Artikal

| Naziv | DN | PN (bar) | G1 | S1 (mm) |
|-----------|-----|----------|-----------|---------|
| WA 006 VB | 6 | 25 | Rp 1/4" | 28,0 |
| WA 010 VB | 10 | 25 | Rp 3/8" | 32,0 |
| WA 013 VB | 13 | 25 | Rp 1/2" | 39,0 |
| WA 020 VB | 20 | 25 | Rp 3/4" | 48,0 |
| WA 025 VB | 25 | 25 | Rp 1" | 55,0 |
| WA 032 VB | 32 | 25 | Rp 1.1/4" | 67,0 |
| WA 040 VB | 40 | 25 | Rp 1.1/2" | 74,0 |
| WA 050 VB | 50 | 25 | Rp 2" | 90,0 |
| WA 065 VB | 65 | 25 | Rp 2.1/2" | 111,0 |
| WA 080 VB | 80 | 25 | Rp 3" | 130,0 |
| WA 100 VB | 100 | 25 | Rp 4" | 151,0 |

Varijante proizvoda

| | |
|-----------------|--|
| WA VB RG | Priključni deo ... VB, crveni mesing, Crveni liv |
| WA VB VA | Priključni deo ... VB VA, plemeniti čelik |