

HK GEH 20 AL

Kućište ventila za uvrtni ventil SAE 2-kraki, aluminijum

HANSA FLEX

Osobine

Materijal	Aluminijum AlZnMgCu1,5
Radni pritisak	maks. 250 bara
Površinska zaštita	eloksiran



Artikal

Naziv	Otvor za ventil	A	Priključak ^{1,3}	C	D	E	F	G	H	I	L	M	Težina
				(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(kg)
HK GEH 38 C0820	C0820	UNF 3/4"	G 3/8"	50	50	29	20	13,5	12	6	9,0	35	0,2
HK GEH 38 C1020	C1020	UNF 7/8"	G 3/8"	60	60	39	24	19,0	15	7	7,5	45	0,4
HK GEH 34 C1020	C1020	UNF 7/8"	G 3/4"	60	60	44	24	21,5	15	7	7,5	45	0,6
HK GEH 12 C1220	C1220	UNF 1.1/16"	G 1/2"	80	80	49	34	26,0	18	9	10,0	60	0,8
HK GEH 34 C1220	C1220	UNF 1.1/16"	G 3/4"	80	80	49	34	26,0	18	9	10,0	60	0,8

je oprema za sledeće proizvode

HK EMDV	2/2- računski ventil sa magnetnim sedištem EMDV
HK RVPS	Ventil za ograničavanje pritiska RVPS
HK PCFC	2-kraki ventil za regulaciju protoka PCFC