

# HK K C E-Motor 24V

## Elektromotor jednosmerne struje 24V

**HANSA FLEX**

### Osobine

|         |  |
|---------|--|
| Verzija | Motor jednosmerne struje za industrijske primene |
| Napon   | 24 V   |



### Artikal

| Naziv     | A     | Ø B   | Verzija           | Sn-aga | Smer okretanja | Broj obrtaja max. | Radni ciklus S2 režim rada | Radni ciklus S3 režim rada | Klasa zaštite | Osovina                  | Težina |
|-----------|-------|-------|-------------------|--------|----------------|-------------------|----------------------------|----------------------------|---------------|--------------------------|--------|
|           | (mm)  | (mm)  |                   | (kW)   |                | (rpm)             | (min)                      | (%)                        |               |                          | (kg)   |
| HK KC 41  | 158,5 | 80,0  | -                 | 0,5    | povratan       | 2800              | 5,0                        | 17,0                       | IP 54         | Tip Y Ø15,6 x 6,5 x 10,5 | 2,60   |
| HK KC 79  | 215,5 | 112,5 | sa ventilatorom   | 2,0    | desnoobrtan    | 2200              | 4,5                        | 10,0                       | IP23          | Tip X Ø17,9 x 8,3 x 9,0  | 7,75   |
| HK KC 92  | 173,5 | 114,0 | -                 | 2,2    | desnoobrtan    | 2600              | 1,2                        | 4,5                        | IP 54         | Tip X Ø17,9 x 8,3 x 9,0  | 6,90   |
| HK KC 94  | 158,5 | 80,0  | -                 | 0,8    | povratan       | 4000              | 2,5                        | 8,0                        | IP 54         | Tip Y Ø15,6 x 6,5 x 10,5 | 2,60   |
| HK KC 95  | 237,0 | 131,0 | -                 | 3,0    | desnoobrtan    | 2600              | 4,0                        | 15,0                       | IP 54         | Tip X Ø16,8 x 8,0 x 7,0  | 12,60  |
| HK KC 97  | 183,0 | 114,0 | -                 | 2,0    | desnoobrtan    | 2200              | 2,0                        | 5,0                        | IP 54         | Tip X Ø17,9 x 8,3 x 9,0  | 7,16   |
| HK KC 103 | 173,5 | 114,0 | sa termo zaštitom | 2,2    | desnoobrtan    | 2600              | 1,2                        | 4,5                        | IP 54         | Tip X Ø17,9 x 8,3 x 9,0  | 6,70   |
| HK KC 104 | 209,0 | 131,0 | sa termo zaštitom | 3,0    | desnoobrtan    | 2600              | 4,0                        | 15,0                       | IP 54         | Tip X Ø16,8 x 8,0 x 7,0  | 12,50  |
| HK KC 111 | 237,0 | 131,0 | sa ventilatorom   | 3,0    | desnoobrtan    | 3300              | 6,0                        | 20,0                       | IP12          | Tip X Ø16,8 x 8,0 x 7,0  | 12,50  |

### Pribor

|          |  |
|----------|--|
| HK K REL | Startni relej za elektromotor jednosmerne struje     |
| HK K CAP | Zaštitni poklopac za elektromotor jednosmerne struje |