

# HK V7 867

8/3-račvasti preklopni ventil

**HANSA FLEX**

## Osobine

|                  |   |
|------------------|---|
| <b>Verzija</b>   | Tip A - srednji položaj otvoren<br>Tip C - srednji položaj zatvoren |
| <b>Materijal</b> | Kućište: liv, unutrašnji delovi od čelika                           |



## Napomena

Rotary slide valves can be pressurised from all sides and are designed to have less internal leakage

## Artikal

| Naziv         | Pritisak max.<br>(bar) | Priključci | Q max.<br>(L/min) | a<br>(mm) | b<br>(mm) | C<br>(mm) | e<br>(mm) | f<br>(mm) | i<br>(mm) | L<br>(mm) | Težina<br>(kg) |
|---------------|------------------------|------------|-------------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|----------------|
| HK V7 867 A06 | 250                    | 3/8"       | 35                | 54        | 77        | 8,5       | 38,5      | 142       | 38,5      | 110       | 2,5            |
| HK V7 867 A08 | 250                    | 1/2"       | 50                | 68        | 90        | 8,5       | 45,0      | 160       | 45,0      | 120       | 3,8            |
| HK V7 867 A12 | 220                    | 3/4"       | 90                | 74        | 95        | 8,5       | 47,5      | 180       | 47,5      | 125       | 5,2            |
| HK V7 867 C06 | 250                    | 3/8"       | 35                | 54        | 77        | 8,5       | 38,5      | 142       | 38,5      | 110       | 2,5            |
| HK V7 867 C08 | 250                    | 1/2"       | 50                | 68        | 90        | 8,5       | 45,0      | 160       | 45,0      | 120       | 3,8            |
| HK V7 867 C12 | 220                    | 3/4"       | 90                | 74        | 95        | 8,5       | 47,5      | 180       | 47,5      | 125       | 5,2            |