


# PVC WAS

Crevo za vodu od PVC-a

**HANSA FLEX**

## Osobine

<b>Oblast primene</b>	Građevinska industrija Agrarna tehnika
<b>Posebne karakteristike</b>	veoma izdržljivo, savitljivo, čvrsto na pritisak i habanje, postojano na UV zrake i vremenske uticaje lako rebrasti spoljni omot
<b>Pogled iznutra</b>	plastificirani PVC, stabilan, veoma fleksibilan, gladak
<b>Umetak</b>	spirala za pojačanje od PVC-a otpornog na pritisak i udarce
<b>spoljni izgled</b>	plastificirani PVC, stabilan, veoma fleksibilan, gladak
<b>Temperatura min.</b>	-5 °C
<b>Temperatura max.</b>	60 °C
<b>Mediji</b>	voda



## Napomena

Npr. sve oznake sa "-6" ne odnose se na debljinu zida

## Artikal

Naziv	col	Unutrašnji-Ø (mm)	Debljina zida (mm)	BD* pri 20°C (bar)	Razorni pritisak (bar)	Vakuum (bar)	min. radijus savijanja (mm)	Dužina rolne (m)
PVC WAS 19-6	3/4"	19	3,0	8,0	25	0,7	85	50
PVC WAS 25-7	1"	25	3,0	7,0	21	0,6	105	50
PVC WAS 32-6	1.1/4"	32	3,0	6,0	21	0,6	125	50
PVC WAS 38-6	1.1/2"	38	3,5	6,0	18	0,6	150	50
PVC WAS 50-5	2"	51	4,5	5,0	15	0,6	205	50
PVC WAS 60-4.5	2.1/2"	60	4,5	4,5	13	0,6	248	50
PVC WAS 76-3.5	3"	76	4,5	3,5	12	0,6	320	50
PVC WAS 90-3.5	3.1/2"	90	5,0	3,0	11	0,6	395	50

BD = radni pritisak