


# BETON 40

Creva za transport betona

**HANSA FLEX**

## Osobine

|                        |   |
|------------------------|---|
| Oblast primene         | Građevinska industrija  |
| Posebne karakteristike | reljefno  |
| Norma                  | DIN 53516   |
| Pogled iznutra         | izolir guma veoma otporna na habanje  |
| Umetak                 | četiri tekstilna umetka veoma otporna na cepanje sa bakarnim nitima               |
| spoljni izgled         | sintetička guma, veoma otporna na habanje, delovanje ozona i atmosferskih prilika |
| Boja                   | crna  |
| Temperatura min.       | -40 °C  |
| Temperatura max.       | 70 °C   |
| Mediji                 | Malter, beton, estrih   |



## Artikal

| Naziv              | col    | Unutrašnji-Ø<br>(mm) | Spoljni-Ø<br>(mm) | Radni pritisak<br>(bar) | Razorni pritisak<br>(bar) | min. radijus savijanja<br>(mm) | Dužina rolne<br>(m) |
|--------------------|--------|----------------------|-------------------|-------------------------|---------------------------|--------------------------------|---------------------|
| BETON 40-25-38     | 1"     | 25,4                 | 38,0              | 40,0                    | 120                       | 110                            | 40                  |
| BETON 40-32-46     | 1.1/4" | 32,0                 | 46,0              | 40,0                    | 120                       | 160                            | 40                  |
| BETON 40-35-49     | 1.3/8" | 35,0                 | 49,0              | 40,0                    | 120                       | 175                            | 40                  |
| BETON 40-38-54     | 1.1/2" | 38,0                 | 54,0              | 40,0                    | 120                       | 190                            | 40                  |
| BETON 40-50-68     | 2"     | 50,8                 | 68,0              | 40,0                    | 120                       | 280                            | 40                  |
| BETON 40-63.5-83.5 | 2.1/2" | 63,5                 | 83,5              | 40,0                    | 120                       | 375                            | 40                  |